

# Numerical Analysis of DAEs from Coupled Circuit and Semiconductor Simulation<sup>\*</sup>

Monica Selva Soto<sup>a</sup> and Caren Tischendorf<sup>f b</sup>

<sup>a</sup>*Humboldt University of Berlin, Institute of Mathematics*

<sup>b</sup>*Technical University of Berlin, Institute of Mathematics*

---

## Abstract

In this work we are interested in the numerical solution of a coupled model of differential algebraic equations (DAEs) and partial differential equations (PDEs). The DAEs describe the behavior of an electrical circuit that contains semiconductor devices and the partial differential equations constitute drift-diffusion equations modelling the semiconductor devices in the circuit.

After space discretization using a finite element method, the coupled system results in a differential-algebraic system with a properly stated leading term. We investigate the structure and the properties of this DAE system. In particular, we develop structural criteria for the DAE index. This is of basic interest since DAE properties like stability, existence and uniqueness of solutions depend strongly on its index.

*Key words:* differential algebraic equation, partial differential equation, tractability index, modified nodal analysis, drift-diffusion equations

---

## 1 Introduction

Nowadays semiconductor devices in an electrical circuit are modelled by small circuits containing basic network elements (capacitors, resistors, inductors, voltage and current sources) described by algebraic and ordinary differential equations. But these equivalent circuits may depend on hundreds of parameters and its correct adjustment has become a very difficult task for the network

---

<sup>\*</sup> Supported by the DFG Research Center “Mathematics for key technologies” (FZT86) in Berlin.

*Email addresses:* [monica@mathematik.hu-berlin.de](mailto:monica@mathematik.hu-berlin.de) (Monica Selva Soto), [tischend@math.tu-berlin.de](mailto:tischend@math.tu-berlin.de) (Caren Tischendorf).

design. This has motivated the idea of using distributed device models, represented by a system of partial differential equations, to describe the behavior of the semiconductor devices within the circuit [1]. The resulting mathematical models couple the differential algebraic equations (DAEs) describing the behavior of the circuit and the partial differential equations (PDEs) modelling semiconductor devices.

In this work we are interested in the numerical solution of the system that is obtained when high frequency devices in an electrical circuit are modelled via drift-diffusion equations. In section 2 the equations resulting from the Modified Nodal Analysis (MNA) of the circuit are explained. The drift-diffusion equations are presented in section 3 as well as its discretization by a finite element method.

Finally, in section 4 the DAE that results from the coupling of the MNA equations and the discrete drift-diffusion equations is constructed and its index is studied. The knowledge about the DAE index allows us to determine the conditions that consistent initial values must satisfy and which numerical methods are feasible for its solution.

## 2 Circuit Equations

The mathematical model that results from Modified Nodal Analysis applied to an electrical network containing resistors, capacitors, inductors and independent voltage and current sources<sup>1</sup> has the form [3]

$$A_C \frac{d}{dt} q_C(A_C^T e, t) + A_R g(A_R^T e, t) + A_L j_L + A_V j_V + A_I i_S(t) = 0, \quad (1)$$

$$\frac{d}{dt} \phi(j_L, t) - A_L^T e = 0, \quad (2)$$

$$A_V^T e - v_S(t) = 0. \quad (3)$$

The unknowns  $e(t) : \mathbb{R} \rightarrow \mathbb{R}^{n_N}$ ,  $j_L(t) : \mathbb{R} \rightarrow \mathbb{R}^{n_L}$  and  $j_V(t) : \mathbb{R} \rightarrow \mathbb{R}^{n_V}$  represent the node potentials, excepting the mass node, the currents through inductors and the currents through voltage sources respectively. The matrices  $A_C, A_R, A_L, A_V$  and  $A_I$  are the element-related (reduced) incidence matrices, they have entries from  $\{-1, 0, 1\}$ . Let the following assumptions on the circuit equations be satisfied in the forthcoming sections:

- (1) the input functions  $v_S(t)$  and  $i_S(t)$ , associated to the independent voltage and current sources respectively, are continuous,

---

<sup>1</sup> Controlled sources have been neglected to simplify matters.

- (2) the functions  $q_C(u, t)$ ,  $\phi(j, t)$  and  $g(u, t)$  are continuously differentiable and have positive definite partial Jacobians

$$C(u, t) = \frac{\partial q_C(u, t)}{\partial u}, \quad L(j, t) = \frac{\partial \phi(j, t)}{\partial j}, \quad G(u, t) = \frac{\partial g(u, t)}{\partial u},$$

- (3) and the circuit contains neither loops of voltage sources only nor cut sets of current sources only. These two conditions hold if and only if the matrices  $A_V$  and  $(A_C \ A_R \ A_L \ A_V)^T$  have full column rank, respectively.

The second assumption concerning the Jacobians reflects local passivity of capacitances, inductances and resistances [4]. The third assumption is necessary from the electric point of view in order to prevent short-circuits.

Under these assumptions it was shown [18,3] that the index of the circuit equations (1)-(3) does not exceed two. More precisely, the index equals two if and only if the circuit contains LI-cut sets (cut sets of inductors and current sources) or CV-loops (loops of capacitors and voltage sources) with at least one voltage source.

Additionally, the previous assumptions allow the circuit equation systems to be formulated as DAEs with a properly stated leading term [15].

### 3 Drift-Diffusion Equations

#### 3.1 Model Equations

We will consider the non-stationary drift-diffusion model of a semiconductor device. For convenience, we formulate the model equations in only one spatial dimension. The segment  $\bar{\Omega} = [0, l] \subset \mathbb{R}$  describes the range of the device, including its contacts and  $t \in [t_a, t_b]$  represents the time. The scaled<sup>2</sup> model equations are given by the Poisson equation

$$-\frac{\partial}{\partial x} \left( \lambda^2 \frac{\partial \psi}{\partial x} \right) = C + p - n, \quad \forall x \in \Omega \quad (4a)$$

for the electrostatic potential  $\psi = \psi(x, t)$  and the continuity equations

$$-\frac{\partial n}{\partial t} + \frac{\partial J_n}{\partial x} = R, \quad \frac{\partial p}{\partial t} + \frac{\partial J_p}{\partial x} = -R, \quad \forall x \in \Omega \quad (4b)$$

<sup>2</sup> Scaling is of importance for the numerical simulation since the original variables have highly different orders of magnitude [17].

for the densities of electrons  $n = n(x, t)$  and holes  $p = p(x, t)$ . The current densities caused by electrons and holes,  $J_n$  and  $J_p$  respectively, can be described as a composition of a drift and a diffusion current,

$$J_n = \mu_n \left( \frac{\partial n}{\partial x} - n \frac{\partial \psi}{\partial x} \right), \quad J_p = -\mu_p \left( \frac{\partial p}{\partial x} + p \frac{\partial \psi}{\partial x} \right). \quad (4c)$$

In (4)  $C = C(x)$  is the doping profile of the semiconductor, the function  $R = R(n, p)$  describes the balance of generation and recombination of electrons and holes and  $\mu_n$  and  $\mu_p$  are assumed to be nonnegative, bounded functions of  $x$ .

The boundary and initial conditions for the model are

$$\psi(0, t) = \frac{1}{U_T} (\psi_{bi}(0) + \omega_0 (e(t))), \quad \psi(l, t) = \frac{1}{U_T} (\psi_{bi}(l) + \omega_l (e(t))), \quad (4d)$$

$$n(0, t) = \frac{C(0) + \sqrt{C(0)^2 + 4\eta_i^2}}{2}, \quad n(l, t) = \frac{C(l) + \sqrt{C(l)^2 + 4\eta_i^2}}{2}, \quad (4e)$$

$$p(0, t) = \frac{-C(0) + \sqrt{C(0)^2 + 4\eta_i^2}}{2}, \quad p(l, t) = \frac{-C(l) + \sqrt{C(l)^2 + 4\eta_i^2}}{2}, \quad (4f)$$

$$n(x, t_a) = n_a(x), \quad p(x, t_a) = p_a(x). \quad (4g)$$

The function  $\psi_{bi}(x)$  is the built-in potential and  $\omega_0, \omega_l$  are the externally applied biases. In this work we want to consider the semiconductor devices as part of an electrical circuit modelled by (1)-(3). Then the biases applied to the semiconductor boundaries depend on the node potentials of the circuit, that is why in (4d) we have written  $\omega_0$  and  $\omega_l$  as functions of  $e$ .

### 3.2 Coupling Current Equation

The electric currents

$$\begin{pmatrix} j_0(t) \\ j_l(t) \end{pmatrix} = \begin{pmatrix} J(0, t) \\ -J(l, t) \end{pmatrix} \text{ with } J(x, t) = J_n(x, t) + J_p(x, t) - \lambda^2 \frac{\partial}{\partial t} \frac{\partial \psi}{\partial x}(x, t),$$

represent the semiconductor's output to the potentials applied to its boundary. The values of  $j_0(t)$  and  $j_l(t)$  satisfy  $j_l(t) = -j_0(t)$ ,  $\forall t \in [t_a, t_b]$ <sup>3</sup>. This means that we may choose one of the terminals of the semiconductor device as reference terminal, let us say the terminal at  $x = l$ , the current through it

<sup>3</sup> This is a consequence of charge conservation. Differentiating (4a) with respect to time and adding (4b) yields  $\frac{\partial J}{\partial x} \equiv 0$ .

may be calculated in terms of the current leaving the other terminal. In what follows we will refer to  $j_0(t)$  as the semiconductor's current.

For a more detailed description of mathematical models for semiconductors and results about existence and uniqueness of solutions of these models see e.g. [16,17,5,13,6,8].

### 3.3 Energy Conservation Equation

In [7] it is pointed out that not only for the numerical solution of this problem, but also for the study of its analytical properties, it is convenient to replace the Poisson equation (4a) by the energy conservation equation

$$\frac{\partial J}{\partial x} = \frac{\partial}{\partial x} \left( J_n + J_p - \lambda^2 \frac{\partial}{\partial x} \frac{\partial \psi}{\partial t} \right) = 0, \quad (5)$$

that is obtained after differentiation of the Poisson equation with respect to time and elimination of  $\frac{\partial n}{\partial t}$  and  $\frac{\partial p}{\partial t}$  from the continuity equations. If the initial value for  $\psi(x, t_a) = \psi_a(x)$  is chosen such that the functions  $\psi_a(x)$ ,  $n_a(x)$  and  $p_a(x)$  satisfy the Poisson equation,

$$- \frac{\partial}{\partial x} \left( \lambda^2 \frac{\partial \psi_a}{\partial x} \right) = C + p_a - n_a \quad (6)$$

the equivalence between (4a) and (5) is guaranteed [7].

### 3.4 Finite Element Method for the Numerical Solution of the Drift-Diffusion Equations

The functions  $(\psi(x, t), n(x, t), p(x, t))$  are a weak solution of (4) if

$$\psi(x, t), n(x, t), p(x, t) \in L_2 \left( (t_a, t_b), H^1(\Omega) \right),$$

have generalized derivatives

$$\frac{\partial \psi}{\partial t} \in L_2([t_a, t_b], H^1(\Omega)), \quad \frac{\partial n}{\partial t}, \frac{\partial p}{\partial t} \in L_2 \left( (t_a, t_b), H^{-1}(\Omega) \right)$$

and satisfy the equations

$$\lambda^2 \int_0^l \frac{\partial \psi}{\partial x} \frac{\partial \varphi}{\partial x} dx = \int_0^l (C - n + p) \varphi dx, \quad (7a)$$

$$- \int_0^l \frac{\partial n}{\partial t} \varphi dx - \int_0^l J_n \frac{\partial \varphi}{\partial x} dx = \int_0^l R \varphi dx, \quad (7b)$$

$$\int_0^l \frac{\partial p}{\partial t} \varphi dx - \int_0^l J_p \frac{\partial \varphi}{\partial x} dx = - \int_0^l R \varphi dx, \quad (7c)$$

for all functions  $\varphi \in H_0^1(\Omega)$  and almost all  $t \in [t_a, t_b]$  as well as the boundary and initial conditions in (4d)-(4g). The integrals involving  $\frac{\partial n}{\partial t}$  and  $\frac{\partial p}{\partial t}$  have to be understood in the sense of distributions.

**Remark** We have asked for more regularity conditions on  $\partial_t \psi$  in order to be able to calculate the current through the semiconductor device. Note that if  $v(x)$  is a function in  $H^1(\Omega)$  that satisfies  $v(0) = 1, v(l) = 0$ , the current  $j_0(t)$  may be written as [7]

$$\begin{aligned} j_0(t) &= J(0, t)h(0) = - \int_{\Omega} J(x, t) \frac{dv}{dx} dx \\ &= - \int_{\Omega} \left( J_n(x, t) + J_p(x, t) - \lambda^2 \frac{\partial \psi}{\partial t} \frac{\partial v}{\partial x}(x, t) \right) dx. \end{aligned} \quad (8)$$

An approximation  $(\psi_h(x, t), n_h(x, t), p_h(x, t))$  of the weak solution of this problem can be determined by the finite element method. For sake of simplicity, let us divide the interval  $[0, l]$  into equally-spaced subintervals  $[x_{i-1}, x_i]$  with  $h = x_i - x_{i-1}$ ,  $x_1 = 0$ ,  $x_m = l$  for  $i = 2, \dots, m$ . In what follows  $\psi_i(t)$ ,  $n_i(t)$  and  $p_i(t)$  denote the approximations to  $\psi(x_i, t)$ ,  $n(x_i, t)$  and  $p(x_i, t)$  ( $i = 1, 2, \dots, m$ ) respectively.

**Discretization of the Poisson equation.** Using the Galerkin ansatz

$$\psi_h(x, t) = \sum_{j=1}^m \psi_j(t) \varphi_j(x), \quad (9)$$

the function  $\psi_h(x, t)$  is obtained by solving the system consisting of the equation (7a) for all basis functions  $\varphi_i(x)$ ,  $i = 2, \dots, m-1$  as well as the boundary and initial conditions in (4d)-(4g). As basis functions  $\varphi_i(x)$  we choose the polynomials of degree one satisfying

$$\varphi_i(x_j) = \begin{cases} 1, & \text{if } i = j, \\ 0, & \text{else.} \end{cases}$$

for all  $j = 1, 2, \dots, m$ . The integral in the right-hand-side of (7a) is approximated with the trapezoidal rule. The equation

$$T\Psi - \left(\frac{h}{\lambda}\right)^2 (C - N + P) - \Psi_0(e) = 0$$

for the unknown coefficients  $\Psi(t) = (\psi_2(t), \dots, \psi_{m-1}(t))^T$  in (9) is obtained. The function  $\Psi_0(e)$  has the components  $\Psi_0(e) = (\psi_1(e) \ 0 \ \dots \ 0 \ \psi_m(e))^T$ ,  $\psi_1 = \psi(0, t)$  and  $\psi_m = \psi(l, t)$  and  $T \in \mathbb{R}^{(m-2) \times (m-2)}$  is the tridiagonal matrix with elements

$$T(i, i) = 2, \quad T(i+1, i) = T(i, i+1) = -1 \quad i = 1, 2, \dots, m-2.$$

The vector  $C$  has components  $C(x_{i+1})$  for  $i = 1, 2, \dots, m-2$  and

$$N(t) = (n_2(t), \dots, n_{m-1}(t))^T, \quad P(t) = (p_2(t), \dots, p_{m-1}(t))^T.$$

**Discretization of the Continuity Equations.** To obtain the approximations  $n_h(x, t)$  and  $p_h(x, t)$  equations (7b) and (7c) are not discretized in the usual way, but by the so-called Scharfetter-Gummel discretization [16]. This way, the area of convergence is usually larger than that one for the standard discretization. The Scharfetter-Gummel discretization is based on the assumption that  $J_n(x, t)$  and  $J_p(x, t)$  can be approximated by constant functions on each subinterval  $(x_{j-1}, x_j]$ ,  $j = 2, \dots, m$ . A description of this discretization in the one dimensional case can be found in [16] and in higher spatial dimensions in [13].

The resulting function  $n_h(x, t)$  that approximates  $n(x, t)$  for  $x \in (x_{j-1}, x_j]$  and  $t \in [t_a, t_b]$  has the form,

$$n_h(x, t) = \begin{cases} n_j \left( \frac{e^{z_j(x-x_{j-1})/h-1}}{e^{z_j-1}} \right) - n_{j-1} \left( \frac{e^{z_j(x-x_{j-1})/h-e^{z_j}}}{e^{z_j-1}} \right), & \text{if } z_j \neq 0, \\ n_{j-1} + (n_j - n_{j-1}) \frac{x-x_{j-1}}{h}, & \text{else.} \end{cases} \quad (10)$$

with  $z_j = \psi_j - \psi_{j-1}$ . The expression for  $p_h(x, t)$  is very similar to this one. The coefficients that define  $n_h(x, t)$  and  $p_h(x, t)$  satisfy

$$-h \frac{d}{dt} n_j + \frac{1}{h} \mu_n^{j+1} f(z_{j+1}) n_{j+1} + \frac{1}{h} \mu_n^j f(-z_j) n_{j-1} - \frac{1}{h} \left( \mu_n^{j+1} f(-z_{j+1}) + \mu_n^j f(z_j) \right) n_j - h R_j = 0, \quad (11)$$

$$h \frac{d}{dt} p_j - \frac{1}{h} \mu_p^{j+1} f(-z_{j+1}) p_{j+1} - \frac{1}{h} \mu_p^j f(z_j) p_{j-1} + \frac{1}{h} \left( \mu_p^{j+1} f(z_{j+1}) + \mu_p^j f(-z_j) \right) p_j + h R_j = 0, \quad (12)$$

$$\begin{aligned} n_1 &= n(0, t), \quad n_m = n(l, t), \quad p_1 = p(0, t), \quad p_m = p(l, t), \\ n_j(t_a) &= n_a(x_j), \quad p_j(t_a) = p_a(x_j), \quad \text{for } j = 2, 3, \dots, m-1. \end{aligned}$$

In the first two equations,

$$f(z) = \begin{cases} \frac{z}{e^z - 1}, & \text{if } z \neq 0, \\ 1, & \text{else.} \end{cases}$$

**Discretization of the Coupling Current Equation.** The current of the semiconductor can be approximated by<sup>4</sup>

$$j_0(t) \approx J_{n,h}(0, t) + J_{p,h}(0, t) - \lambda^2 \frac{\partial}{\partial t} \frac{\partial \psi_h}{\partial x}(0, t) = j_S^c(t) - \frac{d}{dt} j_S^d(t), \quad (13)$$

with

$$j_S^c(t) = J_{n,h}(0, t) + J_{p,h}(0, t) \quad (14)$$

describes the conduction current. The time derivative of  $j_S^d$  forms the discretized displacement current and

$$j_S^d(t) = \beta (\psi_2(t) - \psi_1(t)) = \beta \left( \psi_2(t) - \frac{1}{U_T} [\psi_{bi}(0) + \omega_0(e(t))] \right), \quad \beta = \frac{\lambda^2}{h}. \quad (15)$$

**Remark:** If standard finite elements are used to obtain the approximations  $n_h(x, t)$  and  $p_h(x, t)$ , i.e., if  $n_h(x, t) = \sum_{j=1}^m n_j(t) \varphi_j(x)$  instead of (10), the equations that define the coefficients  $n_j(t)$  and  $p_j(t)$  have the same form as (11) and (12), but  $f(z) = 1 - \frac{z}{2}$ . Note that only when  $z_j = 0$  one obtains the same approximation to  $n(x, t)$  and  $p(x, t)$ ,  $x \in (x_{j-1}, x_j]$ .

For the proof of convergence of the discretization scheme presented here we refer to [16].

### 3.5 Resulting Initial Value Problem

The resulting initial value problem for  $\Psi$ ,  $N$  and  $P$  can be written as the semi-explicit DAE

<sup>4</sup> Choosing the function  $v(x)$  in (8) equal to  $\varphi_1(x)$ .



$$T\Psi - \left(\frac{h}{\lambda}\right)^2 (C - N + P) - \Psi_0(e) = 0, \quad (16a)$$

$$\frac{d}{dt}N - \frac{1}{h^2}g_1(e, \Psi, N) + R(N, P) = 0, \quad (16b)$$

$$\frac{d}{dt}P + \frac{1}{h^2}g_2(e, \Psi, P) + R(N, P) = 0 \quad (16c)$$

with

$$\Psi(t_a) = \Psi_a, \quad N(t_a) = N_a, \quad P(t_a) = P_a$$

The vector  $R$  has components  $R(N(i), P(i))$  for  $i = 1, 2, \dots, m-2$ . The functions  $g_1$  and  $g_2$  are vector-valued functions easily identifiable from the discretized equations. Since their expressions depend on the node potentials of the circuit, we have written them as functions of  $e$  too. The vectors  $N_a$  and  $P_a$  represent the initial values for  $N(t)$  and  $P(t)$ ,  $N_a = (n_a(x_2), \dots, n_a(x_{m-1}))^T$ ,  $P_a = (p_a(x_2), \dots, p_a(x_{m-1}))^T$ . If the initial value for  $\Psi(t)$  is such that

$$\Psi_a = T^{-1} \left(\frac{h}{\lambda}\right)^2 (C - N_a + P_a) + T^{-1}\Psi_0(e_a), \quad (17)$$

then (16) has a locally unique solution.

When the model consisting of the continuity equations and the energy conservation equation is discretized using a finite element method as described above the ODE

$$\frac{d}{dt}\Psi + T^{-1} \frac{1}{\lambda^2} (g_1(e, \Psi, N) + g_2(e, \Psi, P)) - T^{-1} \frac{d}{dt}\Psi_0(e) = 0, \quad (18a)$$

$$\frac{d}{dt}N - \frac{1}{h^2}g_1(e, \Psi, N) + R(N, P) = 0, \quad (18b)$$

$$\frac{d}{dt}P - \frac{1}{h^2}g_2(e, \Psi, P) + R(N, P) = 0. \quad (18c)$$

for the coefficients of  $\psi_h(x, t)$ ,  $n_h(x, t)$  and  $p_h(x, t)$  is obtained.

Note that (16) is a DAE with differentiation index one. If its index is reduced, the ODE (18) is obtained, with the same initial values their exact solutions give us the same approximations to  $\psi(x, t)$ ,  $n(x, t)$  and  $p(x, t)$ .

## 4 Coupling of the Network and Space-Discretized Drift-Diffusion Equations

In [19], the partial differential algebraic equation that results from the coupling between the circuit equations and drift-diffusion equations for the semiconductor devices was studied as abstract differential algebraic system [12]. There it was proved that the coupled system has an index not greater than two if the assumptions in section 2 are satisfied. More precisely, it has index 2 if and only if the circuit contains LI-cut sets (cut sets of inductors and current sources) or CVS-loops (loops of capacitors, voltage sources and semiconductor devices) with at least one voltage source or one semiconductor device.

In this work we study the coupling between the circuit equations and discretized drift-diffusion equations for the semiconductor devices in the circuit and prove that this system has the same index under the same conditions on the circuit as the system considered in [19].

Suppose we want to couple  $n_S$  semiconductor devices, described by discretized drift-diffusion models, to an electrical circuit. The vector  $j_S = (j_{01}, \dots, j_{0n_S})^T$  represents the current through the semiconductors. The incidence of these currents in the circuit may be described by  $A_S j_S$  ( $A_S \in \mathbb{R}^{n_N \times n_S}$ ). Hence, if  $\delta_{i,n}$  represents the  $i$ -th unitary vector of length  $n$ , we find

$$A_S \delta_{k,n_S} = \delta_{i_k, n_N} - \delta_{j_k, n_N}$$

for the  $k$ -th semiconductor device connected to nodes  $i_k$  and  $j_k$ . Furthermore, the biases applied to the semiconductor terminals can also be described in terms of  $A_S$

$$\begin{pmatrix} \omega_{0_k}(e) \\ \omega_{i_k}(e) \end{pmatrix} = \begin{pmatrix} e_{i_k}(t) \\ e_{j_k}(t) \end{pmatrix} = \begin{pmatrix} \delta_{i_k, n_N}^T e \\ \delta_{j_k, n_N}^T e \end{pmatrix} = \begin{pmatrix} \delta_{i_k, n_N}^T e \\ \delta_{i_k, n_N}^T e - \delta_{k, n_S}^T A_S^T e \end{pmatrix}.$$

The system that describes the behavior of the circuit containing  $n_S$  semiconductor devices is formed by the scaled modified nodal analysis equations, where the first one changes to [20]

$$A_C \frac{d}{dt} q_C(A_C^T e, t) + A_R g(A_R^T e, t) + A_L j_L + A_V j_V + A_I i_S(t) + A_S j_S = 0 \quad (19)$$

in order to include the incidence of the semiconductor devices currents into the circuit and the discretized drift-diffusion models of the  $n_S$  semiconductor devices we want to couple to the circuit.

#### 4.1 The Coupled System Formulated as DAE with Porperly Stated Leading Term

For better reading, we will formulate the equation system for circuits with only one semiconductor. But the following results remain the same for circuits with several semiconductors. Suppose the semiconductor is located between the nodes  $i$  and  $j$  with its reference terminal connected to node  $j$ . In this case, the DAE that results from the coupling of the circuit equations with the discretized semiconductor equations reads

$$A_C \frac{d}{dt} q_C(A_C^T e, t) + A_{Rg}(A_R^T e, t) + A_L j_L + A_V j_V + A_I i_S(t) + A_S j_S = 0, \quad (20a)$$

$$\frac{d}{dt} \phi(j_L, t) - A_L^T e = 0, \quad (20b)$$

$$A_V^T e - v_S(t) = 0, \quad (20c)$$

$$j_S^d - \beta \left( \delta_{1,m-2}^T \Psi - \frac{1}{U_T} \psi_{bi}(0) - \frac{1}{U_T} e_i \right) = 0, \quad (20d)$$

$$j_S(t) - j_S^c(e, \Psi, N, P) + \frac{d}{dt} j_S^d = 0, \quad (20e)$$

$$T\Psi - \left(\frac{\hbar}{\lambda}\right)^2 (C - N + P) - \Psi_0(e) = 0, \quad (20f)$$

$$\frac{d}{dt} N - \frac{1}{h^2} g_1(e, \Psi, N) + R(N, P) = 0, \quad (20g)$$

$$\frac{d}{dt} P + \frac{1}{h^2} g_2(e, \Psi, P) + R(N, P) = 0, \quad (20h)$$

where the function  $\Psi_0(e)$  is

$$\Psi_0(e) = \left( \frac{1}{U_T} (\psi_{bi}(0) + e_i), 0, \dots, 0, \frac{1}{U_T} (\psi_{bi}(l) + e_j) \right)^T$$

and  $A_S$  is a column vector,  $A_S = \delta_{i,n_N} - \delta_{j,n_N}$ . The first three equations correspond to the MNA equations (1)-(3) with the first one rewritten as described above (see (19)). The equations (20f)-(20h) are obtained after discretizing the drift-diffusion model in space. Regarding (14), the equations (20d)-(20e) correspond to (13), (15).

In order to study the properties of (20), we will rewrite it as a DAE of the form

$$A \frac{d}{dt} d(y, t) + b(y, t) = 0 \quad (21)$$

with unknowns  $y = (e, j_L, j_V, j_S, j_S^d, \Psi, N, P)^T \in \mathbb{R}^{n_N + n_L + n_V + 1 + 1 + 3(m-2)}$ . The matrix  $A$  and the vectors  $d$  and  $b$  are

$$A = \begin{pmatrix} A_C & 0 & 0 & 0 & 0 \\ 0 & I & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & I & 0 \\ 0 & 0 & 0 & 0 & I \end{pmatrix}, \quad d(y, t) = \begin{pmatrix} q_C(A_C^T e, t) \\ \phi(j_L, t) \\ j_S^d \\ N \\ P \end{pmatrix}, \quad (22a)$$

$$b(y, t) = \begin{pmatrix} A_R g(A_R^T e, t) + A_L j_L + A_V j_V + A_{I_S}(t) + A_S j_S \\ -A_L^T e \\ A_V^T e - v_S(t) \\ j_S^d - \beta \left( \delta_{1, m-2}^T \Psi - \frac{1}{U_T} \psi_{bi}(0) - \frac{1}{U_T} e_i \right) \\ j_S - j_S^c(e, \Psi, N, P, t) \\ T \Psi - \left( \frac{h}{\lambda} \right)^2 (C - N + P) - \Psi_0(e) \\ -\frac{1}{h^2} g_1(e, \Psi, N) + R(N, P) \\ \frac{1}{h^2} g_2(e, \Psi, P) + R(N, P) \end{pmatrix}. \quad (22b)$$

The null space of  $A$  is given by  $\ker A = \ker A_C \times \{0\} \times \{0\} \times \{0\} \times \{0\}$ . The image space of

$$D(y, t) := \frac{\partial d(y, t)}{\partial y} = \begin{pmatrix} C(A_C^T e, t) A_C^T & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & L(j_L, t) & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & I & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & I \end{pmatrix}$$

is  $\text{im } D(y, t) = \text{im } C(A_C^T e, t) A_C^T \times \mathbb{R}^{n_L} \times \mathbb{R} \times \mathbb{R}^{m-2} \times \mathbb{R}^{m-2}$ . The positive definiteness of  $C(A_C^T e, t)$  implies that  $\ker A_C \cap \text{im } C(A_C^T e, t) A_C^T = \{0\}$  and  $\dim(\ker A_C) + \dim(\text{im } C(A_C^T e, t) A_C^T) = n_C$ . Then,  $A$  and  $D(y, t)$  satisfy

$$\ker A \oplus \text{im } D(y, t) = \mathbb{R}^{n_C + n_L + 1 + 2(m-2)}. \quad (23)$$

The DAE (21) with  $A$ ,  $d$  and  $b$  as in (22) has a properly stated leading term [10] if, besides (23), the spaces  $\ker A$  and  $\text{im } D(y, t)$  are independent of  $y$  and have bases that are continuously differentiable in  $t$  and  $d(y, t) \in \text{im } D(y, t)$ ,  $\forall y, \forall t \in [t_a, t_b]$ . In (22),  $\ker A$  is constant, but  $\text{im } D(y, t)$  depends on  $y$ , with  $\tilde{R} = A^+ A$  it can be reformulated as<sup>5</sup>

$$A \frac{d}{dt} (\tilde{R} d(y, t)) + b(y, t) = 0 \quad (24)$$

that has a properly stated leading term [15]. Due to  $A \tilde{R} = A$ , Backward Differentiation Formulas (BDF) and Runge–Kutta (RK) methods applied to (21) and (24) are equivalent and there is no need to compute  $\tilde{R}$  in practice.

#### 4.2 Index of the Discretized Coupled DAE System

Since the network equations usually do not fulfill high smoothness conditions, we use the tractability index concept [15] for the index determination. Additionally, this concept leads us easily to network topological conditions characterizing the index of the discretized coupled DAE system.

**Theorem 1** *If the assumptions in section 2 are satisfied and the circuit contains neither LI-cut sets nor CVS-loops with at least one voltage source or one semiconductor device, the DAE (24) has index one.*

<sup>5</sup>  $A^+$  denotes the Moore-Penrose pseudo inverse of  $A$ .

**PROOF.** We only need to compute the first two links of the matrix chain.

$$G_0(y, t) = A\tilde{R}D = AD, \quad B_0(y, t) = \frac{\partial b}{\partial y}(y, t),$$

$$G_1(y, t) = G_0(y, t) + B_0(y, t)Q_0(y, t)$$

with  $Q_0$  being a projector onto  $N_0 = \ker G_0(y, t)$  and  $P_0 = I - Q_0$ . The DAE (24) has tractability index one if  $G_0$  is singular with constant rank and  $G_1$  is non-singular. Note that

$$N_0(y, t) = \left\{ y \mid y_e \in \ker A_C^T, y_L = 0, y_S^d = 0, y_N = y_P = 0 \right\}$$

and, if  $Q_C$  denotes a projector onto  $\ker A_C^T$ , the matrix

$$Q_0 = \begin{pmatrix} Q_C & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & I & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & I & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

is a projector onto  $N_0$ . Consequently,

$$G_1 = \begin{pmatrix} A_C C(A_C^T e, t) A_C^T + A_R G(A_R^T e, t) A_R^T Q_C & 0 & A_V & A_S & 0 & 0 & 0 & 0 \\ -A_L^T Q_C & L(j_L, t) & 0 & 0 & 0 & 0 & 0 & 0 \\ A_V^T Q_C & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ \frac{\beta}{U_T} \delta_{i, n_N}^T Q_C & 0 & 0 & 0 & 0 & -\beta \delta_{1, m-2}^T & 0 & 0 \\ -\frac{\partial j_S^c}{\partial e} Q_C & 0 & 0 & 1 & 1 & -\frac{\partial j_S^c}{\partial \Psi} & 0 & 0 \\ -\frac{1}{U_T} (\delta_{i, n_N} \ 0 \dots \delta_{j, n_N})^T Q_C & 0 & 0 & 0 & 0 & T & 0 & 0 \\ -\frac{1}{h^2} \frac{\partial g_1}{\partial e} Q_C & 0 & 0 & 0 & 0 & -\frac{1}{h^2} \frac{\partial g_1}{\partial \Psi} & I & 0 \\ \frac{1}{h^2} \frac{\partial g_2}{\partial e} Q_C & 0 & 0 & 0 & 0 & \frac{1}{h^2} \frac{\partial g_2}{\partial \Psi} & 0 & I \end{pmatrix}.$$

The vector  $y = (y_e \ y_L \ y_V \ y_S \ y_S^d \ y_\Psi \ y_N \ y_P)^T$  belongs to  $\ker G_1$  if and only if it satisfies

$$y_L = L(\cdot)^{-1} A_L^T Q_C y_e, \quad y_N = \frac{1}{h^2} \left( \frac{\partial g_1}{\partial e} Q_C y_e + \frac{\partial g_1}{\partial \Psi} y_\Psi \right) \quad (25a)$$

$$y_P = -\frac{1}{h^2} \left( \frac{\partial g_2}{\partial e} Q_C y_e + \frac{\partial g_2}{\partial \Psi} y_\Psi \right), \quad y_S^d = \frac{\partial j_S^c}{\partial e} Q_C y_e - y_S + \frac{\partial j_S^c}{\partial \Psi} y_\Psi, \quad (25b)$$

$$y_\Psi = \frac{1}{U_T} T^{-1} (\delta_{i, n_N} \ 0 \ \dots \ 0 \ \delta_{j, n_N})^T Q_C y_e, \quad (25c)$$

$$A_C C(\cdot) A_C^T y_e + A_R G(\cdot) A_R^T Q_C y_e + A_V y_V + A_S y_S = 0, \quad (25d)$$

$$A_V^T Q_C y_e = 0, \quad (25e)$$

$$\frac{1}{U_T} \delta_{i, n_N}^T Q_C y_e - \delta_{1, m-2}^T y_\Psi = 0. \quad (25f)$$

Inserting  $y_\Psi$  from (25c) into (25f) yields  $A_S^T Q_C y_e = 0$  because  $T$  satisfies<sup>6</sup>  $T^{-1}(1, 1) + T^{-1}(1, m-2) = 1$ .

<sup>6</sup> The matrix  $T$  of size  $k \in \mathbb{N}$  is a symmetric matrix of the form

$$T_k = \begin{pmatrix} \alpha_{k+1} + \alpha_k & -\alpha_k \delta_{1, k-1}^T \\ -\alpha_k \delta_{1, k-1} & T_{k-1} \end{pmatrix}.$$

Let  $Q_{VS}$  be a projector onto  $\ker \begin{pmatrix} A_V^T Q_C \\ A_S^T Q_C \end{pmatrix}$ , then  $Q_{VS} y_e = y_e$  and

$$Q_{VS}^T Q_C^T A_V = 0, \quad Q_{VS}^T Q_C^T A_S = 0.$$

Multiplying equation (25d) by  $Q_{VS}^T Q_C^T$  one obtains that  $y_e$  must also satisfy  $A_R^T Q_C y_e = 0$  (remember that  $G(\cdot)$  is positive definite). Consequently,  $Q_C y_e$  belongs to  $\ker (A_C A_V A_R A_S)^T$  if we take into account that  $A_C^T Q_C y_e = 0$ .

Since  $Q_{CRVS}$  is a projector onto  $\ker (A_C A_R A_V A_S)^T$ , it holds that

$$Q_{CRVS} Q_C y_e = Q_C y_e.$$

Then, equation (25d) implies

$$A_C C(\cdot) A_C^T y_e + A_V y_V + A_S y_S = 0.$$

Multiplying this relation by  $Q_C^T$  one obtains that  $y_V, y_S$  fulfill

$$Q_C^T A_V y_V + Q_C^T A_S y_S = 0,$$

i.e.,  $(y_V y_S)^T \in \ker (Q_C^T A_V Q_C^T A_S)$ .

If the circuit does not have LI-cut sets, the matrix  $(A_C A_R A_V A_S)^T$  has full column rank and  $Q_C y_e = 0$ . If the circuit does not contain CVS-loops with at least one voltage source or one semiconductor device, the matrix  $(Q_C^T A_V Q_C^T A_S)$  has full column rank and then  $(y_V y_S)^T = 0$ . Hence, condition (25d) implies  $y_e \in \ker A_C C(\cdot) A_C^T = \ker A_C^T$ , i.e.,  $y_e = Q_C y_e = 0$ . Finally,  $y_L = 0, y_\Psi = y_N = y_P = 0, y_S^d = 0$  and  $G_1$  is a non-singular matrix.  $\square$

Due to the results in [10] it can be assured that, under the assumptions of Theorem 1, the system (24) has also perturbation index one. Furthermore, if the initial value  $y_a = (e_a, j_{La}, j_{Va}, j_{Sa}, j_{Sa}^d, \Psi_a, N_a, P_a)^T$  satisfies

$$Q_C^T (A_R g(A_R^T e_a, t_a) + A_L j_{La} + A_V j_{Va} + A_I i_S(t_a) + A_S j_{Sa}) = 0, \quad (26a)$$

$$A_V^T e_a - v_S(t_a) = 0, \quad (26b)$$

$$T \Psi_a - \left(\frac{\hbar}{\lambda}\right)^2 (C - N_a + P_a) - \Psi_0(e_a, t_a) = 0, \quad (26c)$$

$$j_{Sa}^d - \beta \left( \delta_{1,m-2}^T \Psi_a - \frac{1}{U_T} (\psi_{bi}(0) + \delta_{i,n_N}^T e_a) \right) = 0 \quad (26d)$$

This means that its inverse is also a symmetric matrix that can be written as  $T_k^{-1} = \begin{pmatrix} a & b^T \\ b & C \end{pmatrix}$  with  $b$  a  $(k-1)$ -dimensional vector and  $C$  a  $(k-1) \times (k-1)$  matrix, the scalar  $a$  and the vector  $b$  must then satisfy the  $k$  relations  $(\alpha_{k+1} + \alpha_k) a - \alpha_k \delta_{1,k-1}^T b = 1$  and  $-\alpha_k \delta_{1,k-1} a + T_{k-1} b = 0$ , adding the last  $k-1$  equations one obtains that  $\alpha_k b_1 + \alpha_1 b_{k-1} = \alpha_k a$  that together with the first relation implies that  $\alpha_{k+1} a + \alpha_1 b_{k-1} = 1$ .

the DAE (24) is uniquely solvable. In addition, BDF and RK methods are convergent for this DAE system. Since  $\text{im } D(y, t)$  is constant, the formulated system is even numerically qualified [11]. For such DAE systems, the decoupling of the inherent dynamics and the discretization commute. This way, the numerical solution inherits important properties known from ODE theory.

**Theorem 2** *If the assumptions in section 2 are satisfied, the circuit contains LI-cut sets or CVS-loops with at least one voltage source or one semiconductor device and  $N$  and  $P$  are always greater than zero, the DAE (24) has index 2.*

**PROOF.** Now, we need to compute one further link of the matrix chain.

$$G_2(y, t) = G_1(y, t) + B_0(y, t)P_0Q_1(y, t)$$

with  $Q_1(y, t)$  being a projector onto  $\ker G_1(y, t)$ . The DAE (24) has index two if  $G_1(y, t)$  is singular and has constant rank and  $G_2(y, t)$  is non-singular for all  $y$  and  $t$  in their definition domain.

Suppose the circuit contains LI-cut sets or CVS-loops with at least one voltage source or one semiconductor device. Let  $Q_{C-VS}$  denote a projector onto  $\ker Q_C^T (A_V \ A_S)$ . Then, the vector  $y$  belongs to  $\ker G_1(y, t)$  if conditions (25a)-(25c) are satisfied and

$$A_C C(\cdot) A_C^T P_C y_e + A_V y_V + A_S y_S = 0, \quad Q_C y_e = Q_{CRVS} Q_C y_e, \quad \begin{pmatrix} y_V \\ y_S \end{pmatrix} = Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix}.$$

Since  $\text{im } Q_{CRVS} \subseteq \text{im } Q_C$ , the projector  $Q_{CRVS}$  may be constructed such that  $\ker Q_C \subseteq \ker Q_{CRVS}$ . The vector  $y \in \ker G_1$  may then be described by conditions (25a)-(25c) and

$$P_C y_e = -H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix}^T, \quad (27a)$$

$$Q_C y_e = Q_{CRVS} (y_e + Q_C y_e - y_e) = Q_{CRVS} y_e, \quad \begin{pmatrix} y_V \\ y_S \end{pmatrix} = Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix}, \quad (27b)$$

where the matrix  $H_C(\cdot) = A_C C(\cdot) A_C^T + Q_C^T Q_C$  is positive definite. Because of  $P_C^T H_C(\cdot) = H_C(\cdot) P_C$ , we get

$$Q_C H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} = H_C(\cdot)^{-1} (Q_C^T A_V \ Q_C^T A_S) Q_{C-VS} = 0$$

$$\text{and } P_C H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} = H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS}.$$

If we denote  $C_L = L(\cdot)^{-1} A_L^T$ ,  $C_N = \frac{1}{h^2} (\frac{\partial g_1}{\partial e} + \frac{\partial g_1}{\partial \Psi} C_\Psi)$ ,  $C_P = -\frac{1}{h^2} (\frac{\partial g_2}{\partial e} + \frac{\partial g_2}{\partial \Psi} C_\Psi)$ ,  $C_{j_S^d} = (\frac{\partial j_S^c}{\partial e} + \frac{\partial j_S^c}{\partial \Psi} C_\Psi)$  and  $C_\Psi = \frac{1}{U_T} T^{-1} (\delta_{i, n_N} \ 0 \ \dots \ 0 \ \delta_{j, n_N})^T$ , a projector  $Q_1$  onto  $\ker G_1$  can be written as

$$Q_1 = \begin{pmatrix} Q_{CRVS} & 0 & -H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_L Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_{j_S^d} Q_{CRVS} & 0 & (0 \dots 0 -1) Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_\Psi Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \\ C_N Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \\ C_P Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}.$$

It can be proved that if  $N$  and  $P$  are always greater than zero the matrix  $G_1$  has constant rank<sup>7</sup>. It remains to show that  $G_2$  is non-singular.

In  $B_0P_0Q_1$  only the first, third and fourth columns are different from zero. The following column vectors represent the first and the third-fourth columns of  $B_0P_0Q_1$ ,

$$\left( \begin{array}{c} A_L C_L Q_{CRVS} \\ 0 \\ C_{j_S^d} Q_{CRVS} \\ -\left(\frac{\partial j_S^c}{\partial N} C_N + \frac{\partial j_S^c}{\partial P} C_P\right) Q_{CRVS} \\ \left(\frac{h}{\lambda}\right)^2 (C_N - C_P) Q_{CRVS} \\ \left(-\frac{1}{h^2} \frac{\partial g_1}{\partial N} + \frac{\partial R}{\partial N}\right) C_N + \frac{\partial R}{\partial P} C_P \\ \left(\frac{1}{h^2} \frac{\partial g_2}{\partial P} + \frac{\partial R}{\partial P}\right) C_P + \frac{\partial R}{\partial N} C_N \end{array} \right) Q_{CRVS}, \quad \left( \begin{array}{c} -A_R G(\cdot) A_R^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ A_L^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ -A_V^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ -\frac{\beta}{U_T} \delta_{i,n_C}^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} + (0 \ \dots \ 0 \ -1) Q_{C-VS} \\ \frac{\partial j_S^c}{\partial e} H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ \frac{1}{U_T} (\delta_{i,n_N} \ 0 \ \dots \ 0 \ \delta_{j,n_N})^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ \frac{1}{h^2} \frac{\partial g_1}{\partial e} H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \\ -\frac{1}{h^2} \frac{\partial g_2}{\partial e} H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \end{array} \right).$$

Suppose the vector  $y = (y_e \ y_L \ y_V \ y_S \ y_{S^d} \ y_\Psi \ y_N \ y_P)^T$  belongs to the null space of  $G_2$ . Multiplying the first equation of  $G_2 y = 0$  by  $Q_{CRVS}^T$  one obtains  $Q_{CRVS}^T A_L L(\cdot)^{-1} A_L^T Q_{CRVS} y_e = 0$ . Since  $L(\cdot)$  is positive definite, this is equivalent to  $A_L^T Q_{CRVS} y_e = 0$ . Due to the assumption that the circuit does not contain cut sets of current sources only, the matrix  $(A_C \ A_L \ A_R \ A_V \ A_S)^T$  has full column rank and, consequently,  $A_L^T Q_{CRVS} y_e = 0 \Leftrightarrow Q_{CRVS} y_e = 0$ .

Inserting  $y_\Psi$  from the sixth equation of  $G_2 y = 0$  into the fourth and taking into account that the matrix  $T$  satisfies that  $T^{-1}(1, 1) + T^{-1}(1, m-2) = 1$ , the components  $y_e, y_V$  and  $y_S$  of  $y$  must satisfy

$$\delta A_S^T \left( Q_C y_e - H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \left( \frac{y_V}{y_S} \right) \right) = \left( 0 \ \dots \ 0 \ \frac{1}{\beta} \right) Q_{C-VS} \left( \frac{y_V}{y_S} \right) \quad (28)$$

where  $\delta = \frac{T^{-1}(1, m-2)}{U_T}$ . The third equation of  $G_2 y = 0$  is

$$A_V^T Q_C y_e - A_V^T H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \left( \frac{y_V}{y_S} \right) = 0. \quad (29)$$

Conditions (28) and (29) may be written as

$$\begin{pmatrix} A_V^T \\ A_S^T \end{pmatrix} Q_C y_e - \begin{pmatrix} A_V^T \\ A_S^T \end{pmatrix} H_C(\cdot)^{-1} (A_V \ A_S) Q_{C-VS} \left( \frac{y_V}{y_S} \right) = \begin{pmatrix} 0 \ \dots \ 0 \ 0 \\ \vdots \\ 0 \ \dots \ 0 \ \frac{1}{\beta\delta} \end{pmatrix} Q_{C-VS} \left( \frac{y_V}{y_S} \right).$$

Multiplying it by  $Q_{C-VS}^T$ , we get

$$Q_{C-VS}^T \left( (A_V \ A_S)^T H_C(\cdot)^{-1} (A_V \ A_S) + \begin{pmatrix} 0 \ \dots \ 0 \ 0 \\ \vdots \\ 0 \ \dots \ 0 \ \frac{1}{\beta\delta} \end{pmatrix} \right) Q_{C-VS} \left( \frac{y_V}{y_S} \right) = 0.$$

<sup>7</sup> By looking at the structure of  $Q_1$  one sees that it has constant rank if the products  $C_N Q_{CRVS}$ ,  $C_P Q_{CRVS}$  and  $C_{j_S^d} Q_{CRVS}$  have constant rank. Using that  $\dim(\text{im } AB) = \dim(\text{im } B) - \dim(\text{im } B \cap \ker A)$  the desired result is obtained.



Because the matrices in this sum are positive semi-definite, it is zero if and only if

$$(A_V \ A_S) Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix} = 0 \quad \text{and} \quad Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix} \in \ker \begin{pmatrix} 0 & \dots & 0 & 0 \\ \vdots & & \vdots & \vdots \\ 0 & \dots & 0 & 0 \\ 0 & \dots & 0 & \frac{1}{\beta\delta} \end{pmatrix}.$$

If  $(v_1 \ v_2)^T = Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix}$ , the above conditions imply  $v_2 = 0$  and  $A_V v_1 + A_S v_2 = 0$ . Since  $A_V$  has full column rank we find  $v_1 = 0$ . Regarding  $Q_{CRVS} y_e = 0$  and  $Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix} = 0$ , it holds that  $B_0 P_0 Q_1 y = 0$ . Thus,  $y$  belongs to  $\ker G_2$  if and only if it belongs to  $\ker G_1$ , i.e., if  $y = Q_1 y$ . But  $Q_{CRVS} y_e = 0$  and  $Q_{C-VS} \begin{pmatrix} y_V \\ y_S \end{pmatrix} = 0$  imply that  $Q_1 y = 0$ , so  $0 = Q_1 y = y$ .  $\square$

Due to the results in [14], it can be assured that, under the assumptions of Theorem 2, the DAE (24) has also perturbation index two.

Following the steps in Theorems 1 and 2, it is easy to prove that the results remain the same for a nonuniform spatial mesh<sup>8</sup> and circuits containing more than one semiconductor device. Furthermore, the index results do not change when standard finite elements are used to approximate the functions  $n(x, t)$  and  $p(x, t)$ .

---

<sup>8</sup> If a nonuniform spatial mesh is considered the first equation in (16) has the form

$$T_h \Psi - \frac{1}{\lambda^2} D_h (C - N + P) - \Psi_{0,h}(e) = 0$$

where  $D_h$  is a diagonal matrix,  $T_h$  is a tridiagonal and symmetric matrix with

$$T_h(i, i) = \frac{1}{h_{i+1}} + \frac{1}{h_{i+2}}, T_h(i, i+1) = -\frac{1}{h_{i+2}}, \quad i = 1, 2, \dots, m-2,$$

$h_i = x_i - x_{i-1}$ ,  $x_1 = 0$ ,  $x_m = l$ . The vector  $\Psi_{0,h}(e)$  is

$$\Psi_{0,h}(e) = \left( -\frac{1}{h_2} \frac{1}{U_T} (\psi_{bi}(0) + e_i), 0, \dots, 0, -\frac{1}{h_m} \frac{1}{U_T} (\psi_{bi}(l) + e_j) \right)^T.$$

When following the steps in lemmata 1 and 2 for proving the index of the coupled system in this case, it is important that  $T_h$  is such that

$$\frac{1}{h_2} T_h^{-1}(1, 1) + \frac{1}{h_m} T_h^{-1}(1, m-2) = 1.$$

The matrix  $T_h$  fulfills this condition as mentioned in the proof of Theorem 1.

### 4.3 Coupled system with discretized energy conservation equation

In most numerical simulations of semiconductor devices the Poisson equation is replaced by the energy conservation formula. In this section we study the properties of the DAE that results when the ODE (18) is coupled to the circuit equations.

**Theorem 3** *The DAE that originates from the coupling of the ODE (18) to the circuit equations can also be written as a DAE with properly stated leading term and has the same index as the DAE previously analyzed.*

**PROOF.** This differential-algebraic system can be written as a DAE of the form  $\bar{A} \frac{d}{dt} \bar{d}(y, t) + \bar{b}(y, t) = 0$  with

$$\bar{A} = \begin{pmatrix} A_C & 0 & 0 & 0 & 0 & 0 \\ 0 & I & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & I & 0 & 0 \\ 0 & 0 & 0 & 0 & I & 0 \\ 0 & 0 & 0 & 0 & 0 & I \end{pmatrix}, \quad \bar{d}(y, t) = \begin{pmatrix} q_C(A_C^T e, t) \\ \phi(j_L, t) \\ j_S^d \\ T\Psi - \Psi_0 \\ N \\ P \end{pmatrix},$$

$$\bar{b}(y, t) = \begin{pmatrix} A_R g(A_R^T e, t) + A_L j_L + A_V j_V + A_I i_S(t) + A_S j_S \\ -A_L^T e \\ A_V^T e - v_S(t) \\ j_S^d - \beta \left( \delta_{1, m-2}^T \Psi - \frac{1}{U_T} (\psi_{b_i}(0) + e_i) \right) \\ j_S - j_S^c(e, \Psi, N, P) \\ \frac{1}{\lambda^2} (g_1(e, \Psi, N) + g_2(e, \Psi, N)) \\ - \frac{1}{h^2} g_1(e, \Psi, N) + R(N, P) \\ \frac{1}{h^2} g_2(e, \Psi, P) + R(N, P) \end{pmatrix}.$$

In this case,  $\ker \bar{A} \oplus \text{im } \bar{D}(y, t) = \mathbb{R}^{n_C + n_L + 3(m-2) + 1}$ . The null space  $\bar{N}_0$  of  $\bar{G}_0$  is

$$\bar{N}_0 = N_0 \cap \left\{ y \mid y_\Psi = \frac{1}{U_T} T^{-1} (\delta_{i, n_N} \ 0 \ \dots \ 0 \ \delta_{j, n_N})^T y_e \right\}$$

and a projector  $\bar{Q}_0$  onto  $\bar{N}_0$  can then be written as

$$\bar{Q}_0 = Q_0 + \begin{pmatrix} 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ \frac{1}{U_T} T^{-1} (\delta_{i, n_N} \ 0 \ \dots \ 0 \ \delta_{j, n_N})^T Q_C & 0 & 0 & 0 & 0 & -I & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}.$$

Following the steps in the proof of Theorem 1 it can be proved that the DAE has index one if the circuit contains neither LI-cut sets nor CVS-loops with at least one voltage source or one semiconductor device. A projector  $\bar{Q}_1$  onto

the null space of  $\bar{G}_1$  is now

$$\bar{Q}_1 = \begin{pmatrix} Q_{CRVS} & 0 & -H_C(\cdot)^{-1}(A_V \ A_S)Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_L Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_{j_S^d} Q_{CRVS} & 0 & (0 \dots 0 -1)Q_{C-VS} & 0 & 0 & 0 & 0 \\ \bar{C}_\Psi Q_{CRVS} & 0 & -C_\Psi H_C(\cdot)^{-1}(A_V \ A_S)Q_{C-VS} & 0 & 0 & 0 & 0 \\ C_N Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \\ C_P Q_{CRVS} & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

with  $\bar{C}_\Psi = C_\Psi - \left(\frac{\hbar}{\lambda}\right)^2 T^{-1} (C_N - C_P)$ .

In a very similar way as in Theorem 2 it can be proved that also in this case the DAE has tractability index two if the circuit contains LI-cut sets or CVS-loops with at least one voltage source or one semiconductor device.  $\square$

## 5 Summary

Electrical circuits containing semiconductor devices can be modelled as a coupled system of differential algebraic and partial differential equations. An approximate solution of such a system can be obtained, as proposed here, by discretizing the partial differential equations in space and solving numerically the resulting DAE. In order to gain information about how to choose consistent initial values, what type of numerical methods may be used for the solution of this DAE, etc., it is important to determine its index.

In the Theorems 1 and 2, the special case of an electrical circuit containing only one semiconductor device modelled by one-dimensional drift-diffusion equations was studied. We proved that the resulting DAE has always index smaller or equal to two. It can be determined by topological conditions on the circuit only. These results can easily be generalized to circuits with more semiconductor devices. We expect that if drift-diffusion equations in two or three spatial dimensions are used to model the semiconductor devices in the circuit the index conditions will be very similar.

Because for the numerical solution of the drift-diffusion equations it is sometimes recommended to replace the Poisson equation by the energy conservation equation we also studied the DAE resulting from the coupling of the circuit equations and the ODE (18). In Theorem 3 it was proved that the results about the tractability index are also valid for this DAE.

For the numerical solution of the coupled system we have made some experiments with a coupling between the device simulator TeSCA [9] developed at Weierstrass Institute in Berlin and DASSL [2]. It is our intention now to implement a software for the solution of the whole DAE that is not based on the

coupling of the two simulators. Comparisons between both approaches will be the subject of a future work.

## Acknowledgements

The authors wish to thank R. Lamour, D. Díaz, A. Jüngel and R. Nürnberg for very fruitful discussions.

## References

- [1] G. Ali, Bartel A., Günther M., Tischendorf C., Elliptic Partial Differential Algebraic Multiphysics Models in Electrical Network Design, *Math. Models Meth. Appl. Sci.*, **13(9)**(2003), pp. 1261-1278.
- [2] Brenan K. E., Campbell S. L., Petzold L. R., *The numerical solution of Initial Value Problems in Ordinary Differential Algebraic Equations*, North Holland Publishing Co., 1989.
- [3] Estévez Schwarz D., Tischendorf C., Structural analysis of electrical circuits and consequences for MNA, *Int. J. Circuit Theory and Applications*, **28**(2000), 131–162.
- [4] Fosséprez M., *Non-linear Circuits: Qualitative Analysis of Non-linear, Non-reciprocal Circuits*, John Wiley & Sons, Chichester, 1992.
- [5] Gajewski H., On Existence, uniqueness and asymptotic behaviour of solutions of the basic equations for carrier transport in semiconductors, *Zeitschrift für Angewandte Mathematik und Mechanik*, **65**(1985), 101–108.
- [6] Gajewski H., Gröger K., Semiconductor equations for variable mobilities based on Boltzmann statistics or Fermi-Dirac statistics, *Math. Nachr.*, **140**(1989), 7–36.
- [7] Gajewski H., Analysis und Numerik von Ladungstransport in Halbleitern, Technical Report, Weierstrass Institut für Angewandte Analysis und Stochastik, 6, 1993.
- [8] Gajewski H., On the uniqueness of solutions to the Drift-Diffusion model of semiconductors devices, *Mathematical Models and Methods in Applied Sciences*, **4**(1994), 121–133.
- [9] Gajewski H., Heinemann B., Langmach H., Nürnberg R., Kaiser H.-Chr., Bandelow U., WIAS-TeSCA. Two dimensional Semi-Conductor Analysis Package, Manual, Weierstrass Institut für Angewandte Analysis und Stochastik, 1999.

- [10] Higuera I., März R., Differential algebraic equations with properly stated leading terms, to appear in *Comp. Math. Appl.*, 2004.
- [11] Higuera I., März R., Tischendorf C., Stability preserving integration of index-1 DAEs, *APNUM*, **45**(2003), pp. 175-200.
- [12] Lamour R., März R., Tischendorf C., PDAEs and Further Mixed Systems as Abstract Differential Algebraic Systems, Technical Report, Institute of Mathematics, Humboldt University of Berlin, 11, 2001.
- [13] Markovich P.A., *The stationary semiconductor device equations*, Springer-Verlag, 1986.
- [14] März R., Nonlinear differential-algebraic equations with properly formulated leading term, Technical Report, Humboldt University of Berlin, 3, 2001.
- [15] März R., Differential algebraic systems with properly stated leading term and MNA equations, in: K. Antreich, R. Burlisch, A. Gilg and P. Rentrop (Eds), *Modeling, Simulation and Optimization of Integrated Circuits*, International Series of Numerical Mathematics, Vol. 146, 2003, pp. 135-151.
- [16] Mock M. S., *Analysis of Mathematical Models of Semiconductor Devices*, Boole Press, 1983.
- [17] Selberherr S., *Analysis and simulation of semiconductor devices*, Springer-Verlag, 1984.
- [18] Tischendorf C., Topological index calculation of DAEs in circuit simulation, *Surv. Math. Ind.*, **8**(1999), 187–199.
- [19] Tischendorf C., Modeling circuit systems coupled with distributed semiconductor equations, in: K. Antreich, R. Burlisch, A. Gilg and P. Rentrop (Eds), *Modeling, Simulation and Optimization of Integrated Circuits*, International Series of Numerical Mathematics, Vol. 146, 2003, pp. 229-247.
- [20] Tischendorf C., Coupled Systems of Differential Algebraic and Partial Differential Equations in Circuit and Device Simulation, Habilitation Thesis, Humboldt University of Berlin, 2003.