

1 **DECIDING ROBUST FEASIBILITY AND INFEASIBILITY USING A**  
2 **SET CONTAINMENT APPROACH:**  
3 **AN APPLICATION TO STATIONARY PASSIVE GAS NETWORK**  
4 **OPERATIONS\***

5 DENIS ASSMANN<sup>†</sup>, FRAUKE LIERS<sup>†</sup>, MICHAEL STINGL<sup>†</sup>, AND JUAN VERA<sup>‡</sup>

6 **Abstract.** In this paper we study feasibility and infeasibility of nonlinear two-stage fully ad-  
7 justable robust feasibility problems with an empty first stage. This is equivalent to deciding whether  
8 the uncertainty set is contained within the projection of the feasible region onto the uncertainty-  
9 space. Moreover, the considered sets are assumed to be described by polynomials. For answering  
10 this question, two very general approaches using methods from polynomial optimization are pre-  
11 sented — one for showing feasibility and one for showing infeasibility. The developed methods are  
12 approximated through sum of squares polynomials and solved using semidefinite programs.  
13 Deciding robust feasibility and infeasibility is important for gas network operations, which is a non-  
14 convex feasibility problem where the feasible set is described by a composition of polynomials with  
15 the absolute value function. Concerning the gas network problem, different topologies are consid-  
16 ered. It is shown that a tree structured network can be decided exactly using linear programming.  
17 Furthermore, a method is presented to reduce a tree network with one additional arc to a single cycle  
18 network. In this case, the problem can be decided by eliminating the absolute value functions and  
19 solving the resulting linearly many polynomial optimization problems.  
20 Lastly, the effectivity of the methods is tested on a variety of small cyclic networks. It turns out that  
21 for instances where robust feasibility or infeasibility can be decided successfully, level 2 or level 3 of  
22 the Lasserre relaxation hierarchy typically is sufficient.

23 **Key words.** polynomial optimization, robust optimization, natural gas transport

24 **AMS subject classifications.** 90C22, 90C30, 90C34, 90C99

25 **1. Introduction.** In this paper we study feasibility and infeasibility of nonlinear  
26 two-stage fully adjustable robust feasibility problems with an empty first stage. We  
27 further assume that the considered sets, i.e., the uncertainty set and the set of feasible  
28 solutions, are described by polynomials. The overall goal of the considered uncertain  
29 problem is to answer the question whether for all possible realizations of the data  
30  $u \in \mathcal{U} \subseteq \mathbb{R}^{n_1}$ , there is always a solution  $x(u) \in \mathbb{R}^{n_2}$  ( $n_1, n_2 \in \mathbb{N}$ ). If this question can  
31 be answered positively, we call the problem “robust feasible” and “robust infeasible”  
32 otherwise. Given some vector-valued polynomial constraint functions  $f: \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \rightarrow$   
33  $\mathbb{R}^{k_1}$  and  $g: \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \rightarrow \mathbb{R}^{k_2}$ , the feasibility question can be formulated as

34 (1) 
$$\forall u \in \mathcal{U} \exists x \in \mathbb{R}^{n_2} \text{ such that } f(u, x) = 0, g(u, x) \leq 0.$$

35 This question can be answered by checking whether

36 
$$\mathcal{U} \subseteq \text{Proj}_u(\{(u, x) \mid f(u, x) = 0, g(u, x) \leq 0\}).$$

37 Since set containment implies that each value of  $u \in \mathcal{U}$  is associated with at least  
38 one feasible solution  $x(u)$ , the expression in (1) holds. Compared to set containment

---

\*Submitted to the editors DATE.

**Funding:** The authors thank the DFG for their support within Project B06 in CRC TRR 154. This work was supported by a STSM Grant from COST Action TD1207. Furthermore, the authors would like to acknowledge the support of the ZISC.

<sup>†</sup>Lehrstuhl für Wirtschaftsmathematik, Department Mathematik, Friedrich-Alexander-Universität Erlangen-Nürnberg, Cauerstraße 11, 91058 Erlangen, Germany ([denis.assmann@fau.de](mailto:denis.assmann@fau.de), [frauke.liers@fau.de](mailto:frauke.liers@fau.de), [michael.stingl@fau.de](mailto:michael.stingl@fau.de)).

<sup>‡</sup>Department of Econometrics and Operations Research, Tilburg University, 5000 LE Tilburg, The Netherlands ([j.c.veralizcano@uvt.nl](mailto:j.c.veralizcano@uvt.nl)).

39 problems where the constraint-wise description of each set is known, the description  
 40 of the projection is typically not available or too expensive to compute. We address  
 41 this additional challenge in our methods without an explicit construction of the pro-  
 42 jection. Solving this type of problem is a first step towards more complex two-stage  
 43 robust optimization tasks with non-empty first stage and polynomial second stage.  
 44 Due to the polynomial structure of the uncertain problem, this leads to polynomial  
 45 optimization problems. There are several approaches in the literature on how to con-  
 46 struct relaxations of general polynomial problems [14, 19, 21, 26]. Given a concrete  
 47 instance, we use the well known Lasserre SDP relaxation hierarchy [14, 21] and solve  
 48 the resulting semidefinite problems to global optimality. Since the feasibility question  
 49 is tackled using a relaxation approach, the constructed problems can't generally give  
 50 reliable answers for both feasibility and infeasibility at the same time. For example,  
 51 due to the relaxation a problem might give a negative answer although the problem  
 52 is in fact feasible and vice versa. This makes it necessary to develop two approaches:  
 53 one for deciding feasibility and one for deciding infeasibility.

54 Our contribution towards solving this problem is twofold:  
 55 First, Lemma 3.6 shows how the problem can still be solved even if an algebraic  
 56 description of the projected set is not known. This leads to a series of polynomial  
 57 optimization problems which can be solved approximately using the Lasserre SDP  
 58 relaxation hierarchy [14]. We call this the *feasibility approach*.  
 59 Second, we develop another polynomial optimization problem to certify infeasibility of  
 60 the set containment problem in Lemma 3.2. Again, this so called *infeasibility approach*  
 61 works without the algebraic description the projected set.

62 Our methods are inspired by a gas network problem under uncertainty which is a  
 63 non-convex feasibility problem where the feasible set is described by a composition of  
 64 polynomials with the absolute value function. The studied gas network problem can  
 65 be interpreted as a linear network flow problem with additional variables modelling  
 66 the nodal pressure and constraints linking the pressure difference of two adjacent  
 67 nodes with the flow over the connecting arc. For an overview on the problems arising  
 68 in the operation of gas networks, the reader is referred to [24]. A special property of  
 69 the considered type of gas network problems is that the feasible flows are uniquely  
 70 determined by a piecewise polynomial equation system. As a consequence, any fixed  
 71 uncertainty  $u$  leads to a unique flow solution  $x(u)$  of the problem (which might still  
 72 be violated by the constraints). Exploiting this property enables us to circumvent an  
 73 explicit construction of the projected set.

74 The methods we develop can be applied to two-stage nonlinear robust optimiza-  
 75 tion problems with an empty first stage and polynomial second stage. In the case of  
 76 gas network operation, possible first stage variables can model the decisions of the  
 77 network operator concerning for example the state of the gas compressor machines.  
 78 For deciding robust feasibility, we additionally assume that the solutions  $x$  depend  
 79 uniquely on the uncertain data  $u$ . For several reasons, the application of standard  
 80 robust optimization techniques is difficult in this case. While there are some concepts  
 81 for solving nonlinear robust optimization tasks [2], they typically require convex non-  
 82 linear functions for an exact tractable reformulation. The canonical way to deal with  
 83 second stage (“adjustable”) variables is by replacing them with a decision rule of  
 84 predetermined structure [3] which may result in conservative solutions. If the prob-  
 85 lem has random recourse, i.e., there are products of uncertain parameters and second  
 86 stage variables, even the introduction of simple affine linear decision rules can only  
 87 be done approximately [3]. Another challenge is posed by the assumption that solu-  
 88 tions  $x$  depend uniquely on the uncertain data. Thus, this functions  $x(u)$  is the only

feasible decision rule for the second stage variables. We therefore use the projection idea to avoid constructing the correct decision rule explicitly. Regarding the general computation complexity of set containment problems with convex sets, we refer to [9]. A more practical treatment for polyhedra and special convex sets is given by [17]. Furthermore, a treatment of set containment regarding polytopes and spectahedra can be found in [13]. This work is further extended in [12] to encompass projections of polytopes and spectahedra.

Concerning the problem of set containment between basic semialgebraic sets, the general purpose doubly-exponential cylindrical algebraic decomposition algorithm [4] can be used to eliminate quantifiers from polynomial systems. It therefore could be used for the combination of projection and set containment.

Optimal control is another field where the problem of set containment of basic semialgebraic sets occurs. It can be treated through relaxations of the real Positivstellensatz [11]. This approach is in some sense similar to the techniques in this paper but cannot be applied to the projected problem.

This work is structured as follows: In [section 2](#), a general introduction to the problem setting is given. In order to showcase the issue at hand and the solution ideas of this work, a linear network flow problem under uncertainty is presented in [subsection 2.1](#). Next, our solution approaches for the set containment problem are laid out in [section 3](#). Our main ideas, the infeasibility and feasibility approach for deciding set containment, are presented in [subsection 3.1](#) and [subsection 3.2](#), respectively. [Section 4](#) shows a practical application of the developed methods to the uncertain gas transport problem. The problem together with some important results concerning the nominal case are presented in [subsection 4.1](#). Next, the robust problem is solved for the special case of tree structured networks in [subsection 4.2](#). The application part concludes in [subsection 4.3](#) with a list of techniques to remove absolute value functions arising in the gas context. After converting the problem to a purely polynomial formulation, the developed set containment methods can be applied. The practical feasibility of the ideas is demonstrated in [section 5](#) through a series of numerical results using a number of small network problems. This work closes with a summary in [section 6](#).

**2. Problem Description and the Setting Studied Here.** A class of parameterized nonlinear feasibility problems is studied. Let  $f: \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \rightarrow \mathbb{R}^{k_1}$  and  $g: \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \rightarrow \mathbb{R}^{k_2}$  ( $n_1, n_2, k_1, k_2 \in \mathbb{N}$ ) be some (possibly nonlinear) constraint functions. For the solution approaches presented in this paper, these functions are assumed to be polynomial. The first argument of each function is assumed to be a parameter  $u$  which is shared by both  $f$  and  $g$ . This parameter is often called the *uncertainty* or *uncertain data* of the problem which is an element of an a priori given *uncertainty set*  $\mathcal{U} \subseteq \mathbb{R}^{n_1}$ . Our goal is to answer the question whether for all possible realizations  $u \in \mathcal{U}$  there is always a feasible solution  $x \in \mathbb{R}^{n_2}$  of the problem:

$$(2) \quad \forall u \in \mathcal{U} \exists x \in \mathbb{R}^{n_2} \text{ such that } f(u, x) = 0, g(u, x) \leq 0.$$

Let  $\mathcal{B} = \{(u, x) \in \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \mid f(u, x) = 0, g(u, x) \leq 0\}$  be the set of all feasible pairs of uncertain data  $u$  and problem solution  $x$ . Question (2) can be answered by checking whether the set containment condition

$$\mathcal{U} \subseteq \text{Proj}_u(\mathcal{B})$$

holds. Since set containment implies that each value of  $u \in \mathcal{U}$  is associated with at least one feasible solution  $x(u)$ , the expression in (2) is satisfied.

136 In the next subsection, the set containment idea is further explored on the example  
 137 of a simple linear network flow problem over a tree.

138 **2.1. Introductory Example: Linear Flow Problem over a Tree.** We want  
 139 to further illustrate the problem and its possible solution approaches by means of a  
 140 simple example. Let a linear flow problem be given over a tree with lower and upper  
 141 edge capacities and uncertain demands. The data appears as an uncertain right hand  
 142 side of the flow balance equations. We assume that the demand  $u$  of all nodes except  
 143 some fixed root node fluctuates within a hypercube  $\mathcal{U}$ . The model can then be stated  
 144 as

$$145 \quad \forall u \in \mathcal{U} \exists x: \begin{cases} Ax = u, \\ \underline{x} \leq x \leq \bar{x} \end{cases}$$

146 for some non-singular matrix  $A$ , see [subsection 4.1](#) for details. After substituting  
 147  $x = A^{-1}u$ , the problem is equivalent to

$$148 \quad \forall u \in \mathcal{U}: \underline{x} \leq A^{-1}u \leq \bar{x},$$

149 or

$$150 \quad (3) \quad \mathcal{U} \subseteq \{u \mid \underline{x} \leq A^{-1}u \leq \bar{x}\} = \text{Proj}_u(\{(u, x) \mid Ax = u, \underline{x} \leq x \leq \bar{x}\})$$

151 when stated as a set containment problem. Since both sets are polyhedral, the ques-  
 152 tion can be decided by optimizing over the remaining constraint functions: if

$$153 \quad \max_{u \in \mathcal{U}} (A^{-1}u)_i \leq \bar{x}_i \quad \text{and} \quad \min_{u \in \mathcal{U}} (A^{-1}u)_i \geq \underline{x}_i$$

155 hold for all  $i = 1, \dots, n_1$ , so does the set containment condition. By using linear  
 156 duality, these inequalities can be checked with one linear optimization problem, see  
 157 [Lemma 4.4](#).

158 In this example, we were able to exploit the simple structure to directly construct  
 159 the projected set in equation (3). For more complicated linear or nonlinear constraints,  
 160 this may not always be possible or computationally too expensive. For treating the  
 161 arising problems, we will use ideas from polynomial optimization.

162 **2.2. Polynomial Optimization.** Let  $\mathbb{R}[x] := \mathbb{R}[x_1, \dots, x_n]$  denote the set of  
 163 polynomials in  $n$  variables with real coefficients. A polynomial  $p \in \mathbb{R}[x]$  is defined as  
 164  $p(x) = \sum_{\alpha \in \mathbb{N}_0^n} p_\alpha x^\alpha$  with coefficients  $p_\alpha \in \mathbb{R}$  and monomials  $x^\alpha = (x_1^{\alpha_1}, \dots, x_n^{\alpha_n})$  for  
 165  $\alpha \in \mathbb{N}_0^n$ . With  $|\alpha| = \sum_i \alpha_i$ , define the degree of  $p$  as  $\deg(p) := \max\{|\alpha| \mid p_\alpha \neq 0\}$ .  
 166 Let  $\mathcal{P}[S] = \{p \in \mathbb{R}[x] \mid p(x) \geq 0, \forall x \in S\}$  (resp.  $\mathcal{P} = \mathcal{P}[\mathbb{R}^n]$ ) denote the set of  
 167 nonnegative polynomials on a subset  $S \subseteq \mathbb{R}^n$  (resp. on  $\mathbb{R}^n$ ).

168 Polynomial optimization is the problem of optimizing a polynomial over a *basic*  
 169 *semi-algebraic set*  $S = \{x \in \mathbb{R}^n : q_1(x) \geq 0, \dots, q_m(x) \geq 0\}$ . Every polynomial opti-  
 170 mization problem can be written as optimizing a linear function over the cone  $\mathcal{P}[S]$  of  
 171 nonnegative polynomials on  $S$ . Optimizing over  $\mathcal{P}[S]$  is  $\mathcal{NP}$ -hard for most (interest-  
 172 ing) choices of  $S$ . Hierarchies of tractable approximations of the cone  $\mathcal{P}[S]$  are typi-  
 173 cally constructed through sum of squares (SOS) relaxations ([14]), which correspond  
 174 to semidefinite liftings of subsets of  $\mathcal{P}[S]$  into higher dimensions. The construction is  
 175 motivated by results related to representations of non-negative polynomials as SOS  
 176 and the dual theory of moments. The convergence of Lasserre's method is based on

177 the assumption that  $\{q_1, \dots, q_m\}$ , the given description of  $S$ , allows the application  
 178 of Putinar's Theorem [23]. In particular, it assumes  $S$  is compact.

179 To construct Lasserre's hierarchy, the *truncated quadratic module* of level  $d$  is  
 180 defined as

$$181 \quad (4) \quad M_d[\mathcal{S}] = \left\{ \sigma_0(x) + \sum_{i=1}^m \sigma_i(x)q_i(x) \mid \begin{array}{l} \sigma_0, \sigma_i \text{ is sum of squares} \\ \deg(\sigma_0) \leq 2d, \deg(\sigma_i q_i) \leq 2d \end{array} \right\}.$$

182 This set can be expressed as the feasible region of  $m+1$  semidefinite constraints with  
 183 linear equalities over the coefficients of  $\sigma_0$  and  $\sigma_i q_i$  [26]. Furthermore, as  $M_d[\mathcal{S}] \subseteq$   
 184  $M_{d+1}[\mathcal{S}] \subseteq \mathcal{P}[\mathcal{S}]$  holds, this set can be used as an approximation for  $\mathcal{P}[\mathcal{S}]$ . Notice that  
 185 by increasing  $d$ , a sequence of semidefinite relaxations of increasing size is obtained.

186 Lasserre shows [14] that under mild conditions, the optimal objective value over  
 187 these relaxations converges to the optimal value over  $\mathcal{P}[\mathcal{S}]$ . [Proposition 2.1](#) states the  
 188 result using our notation.

189 **PROPOSITION 2.1.** *Let  $q_0, q_1, \dots, q_m \in \mathbb{R}[x]$  be given. Let  $\mathcal{S} = \{x \in \mathbb{R}^n : q_1(x) \geq$   
 190  $0, \dots, q_m(x) \geq 0\}$ . Consider the optimization problem  $\mu = \inf\{q_0^T p : p \in \mathcal{P}[\mathcal{S}]\}$  and  
 191 the sequence of relaxations  $\mu_d = \inf\{q_0^T p : p \in M_d[\mathcal{S}]\}$ . Assume there exists a real-  
 192 valued polynomial  $u(x) = \sigma_0 + \sum_{i=1}^m g_i \sigma_i$  where  $\sigma_i$  is SOS for all  $i$  and such that  
 193  $\{x : u(x) \geq 0\}$  is compact.*

194 *Then (Putinar [23])*

$$195 \quad M_1[\mathcal{S}] \subseteq M_2[\mathcal{S}] \subseteq \dots \subseteq M_d[\mathcal{S}] \subseteq \dots \subseteq \mathcal{P}[\mathcal{S}]$$

$$196 \quad \text{and } \{p \in \mathbb{R}[x] : p(s) > 0 \forall s \in \mathcal{S}\} \subseteq \bigcup_{d>0} M_d[\mathcal{S}]$$

197 *and therefore (Lasserre [14])*

$$199 \quad \mu^1 \leq \mu^2 \leq \dots \leq \mu^d \leq \dots \leq \mu \text{ and } \mu^r \rightarrow \mu \text{ as } d \rightarrow \infty.$$

200 In other words, using Lasserre's hierarchy for general polynomial optimization prob-  
 201 lems one may approximate the global optimal value  $\mu$  as closely as desired by solving  
 202 a sequence of semidefinite problems with increasing size of the semidefinite matrices  
 203 and number of constraints.

### 204 3. Deciding Robust Feasibility and Infeasibility for the General Case.

205 In this section, the two approaches for deciding robustness are developed. We present  
 206 a method for certifying infeasibility in [subsection 3.1](#) as well as a method for proving  
 207 feasibility in [subsection 3.2](#).

208 **3.1. A Set Containment Approach for Certifying Infeasibility.** A robust  
 209 optimization problem said to be infeasible if a scenario  $\hat{u} \in \mathcal{U}$  exists whose correspond-  
 210 ing problem is infeasible. We first introduce an abstract model involving arbitrary  
 211 functions for solving this problem. The model is then adapted to the considered case  
 212 of polynomial functions. With this approach, negative certificates for set contain-  
 213 ment of two basic semi-algebraic sets can be found. Recall that a set  $\mathcal{S}$  is called *basic*  
 214 *semi-algebraic*, if it is of the form

$$215 \quad \mathcal{S} = \{x \mid p_i(x) \geq 0, \quad i = 1, \dots, n\}.$$

216 where  $p_i(x) \in \mathbb{R}[x]$  for  $i = 1, \dots, n$  ( $n \in \mathbb{N}$ ) are polynomials. For any set  $\mathcal{S}$ , let  
 217  $\mathcal{F}[\mathcal{S}] := \{f : \mathbb{R}^n \rightarrow \mathbb{R} \mid f(x) \geq 0 \text{ for } x \in \mathcal{S}\}$  be the set of all nonnegative functions on

218  $\mathcal{S}$ . The set  $\mathcal{F}[\mathcal{S}]$  is nonempty since it always contains  $h(x) \equiv 0$ , regardless of the  
 219 particular choice of  $\mathcal{S}$ .

220 Let  $\mathcal{S}_1, \mathcal{S}_2$  be any subsets of  $\mathbb{R}^n$ . It is clear that

$$221 \quad (5) \quad \mathcal{S}_1 \not\subseteq \mathcal{S}_2 \iff \exists x \in \mathcal{S}_1 : x \notin \mathcal{S}_2 \iff \mathcal{S}_1 \setminus \mathcal{S}_2 \neq \emptyset.$$

222 Using this definition, (5) can be extended to

$$223 \quad \mathcal{S}_1 \setminus \mathcal{S}_2 \neq \emptyset \iff \exists f \in \mathcal{F}[\mathcal{S}_2] \text{ and } x \in \mathcal{S}_1 \text{ such that } f(x) < 0.$$

224 The last expression can be rewritten using an optimization problem. Let the abstract  
 225 separation problem (ASep) be defined as

$$226 \quad (\text{ASep}) \quad \begin{aligned} & \inf f(x), \\ & x \in \mathcal{S}_1, \\ & f \in \mathcal{F}[\mathcal{S}_2]. \end{aligned}$$

227 We employ the usual definition of  $\inf_X f(x) = +\infty$  if  $X = \emptyset$ . For the optimal value  
 228 of (ASep) it holds that

$$229 \quad \inf_{x \in \mathcal{S}_1, f \in \mathcal{F}[\mathcal{S}_2]} f(x) = \begin{cases} +\infty, & \text{if } \mathcal{S}_1 = \emptyset \\ 0, & \text{if } \mathcal{S}_1 \neq \emptyset \text{ and } \mathcal{S}_1 \subseteq \mathcal{S}_2, \\ -\infty, & \text{if } \mathcal{S}_1 \neq \emptyset \text{ and } \mathcal{S}_1 \not\subseteq \mathcal{S}_2. \end{cases}$$

230 Combining the first two cases yields

$$231 \quad (6) \quad \mathcal{S}_1 \not\subseteq \mathcal{S}_2 \iff \inf_{x \in \mathcal{S}_1, f \in \mathcal{F}[\mathcal{S}_2]} f(x) = -\infty.$$

232 In order to tackle this optimization task in practice, the abstract problem is  
 233 approximated by a polynomial optimization problem. We first replace the set of  
 234 functions  $\mathcal{F}[\mathcal{S}_2]$  by the set

$$235 \quad \mathcal{P}[\mathcal{S}_2] := \{p \in \mathbb{R}[x] \mid p(x) \geq 0 \text{ for } x \in \mathcal{S}_2\}$$

236 of polynomials that are nonnegative on  $\mathcal{S}_2$ . Since both  $p$  and  $x$  are variables,  $p(x)$   
 237 cannot be cast directly as part of a polynomial optimization problem. Therefore,  
 238 instead of minimizing  $p(x)$ , the integral of  $p$  over  $\mathcal{S}_1$  is minimized:

$$239 \quad \begin{aligned} & \inf_p \int_{\mathcal{S}_1} p(x) \, d\mu, \\ & p \in \mathcal{P}[\mathcal{S}_2]. \end{aligned}$$

240 Using the definition  $p(x) = \sum_{\alpha} p_{\alpha} x^{\alpha}$ , the objective can be rewritten in terms of the  
 241 moments of  $\mu$ :

$$242 \quad (\text{PolySep}) \quad \begin{aligned} & \inf_p \int_{\mathcal{S}_1} p \, d\mu = \inf_p \sum_{\alpha} p_{\alpha} \int_{\mathcal{S}_1} x^{\alpha} \, d\mu \\ & p \in \mathcal{P}[\mathcal{S}_2]. \end{aligned}$$

243 Since the moments  $\int_{\mathcal{S}_1} x^{\alpha} \, d\mu$  can be calculated in advance, the objective of (PolySep)  
 244 is a linear function in  $p$ .

245 We call this problem the polynomial separation problem. If there exists  $p$ , such  
 246 that the integral over  $\mathcal{S}_1$  is negative, there must be some point  $x \in \mathcal{S}_1$  with  $p(x) < 0$ .  
 247 Then, by definition of  $p$ , it holds that  $x \notin \mathcal{S}_2$ .

248 The integration is a weaker test for the existence of an  $x \in \mathcal{S}_1$  with  $p(x) < 0$   
 249 than just evaluating  $p(x)$  (see Lemma 3.1). For practical applications, the moments  
 250  $\int_{\mathcal{S}_1} x^\alpha d\mu$  need to be available. With respect to the presented robust gas network prob-  
 251 lem, this is no limitation since  $\mathcal{S}_1 = \mathcal{U}$  is a hypercube.

252 The next lemma identifies conditions for  $\mathcal{S}_1, \mathcal{S}_2$  for which a polynomial  $p \in \mathcal{P}[\mathcal{S}_2]$   
 253 exists with  $\int_{\mathcal{S}_1} p(x) d\mu < 0$ . This means that under these conditions, problems (ASep)  
 254 and (PolySep) are equivalent.

255 **LEMMA 3.1.** *Let  $\mathcal{S}_1, \mathcal{S}_2 \subseteq \mathbb{R}^n$  be two bounded sets with  $\mathcal{S}_1 \setminus \mathcal{S}_2 \neq \emptyset$ . Suppose that*  
 256  *$\mathcal{S}_1 \setminus \mathcal{S}_2$  contains an open subset.*  
 257 *Then there exists a polynomial  $p \in \mathcal{P}[\mathcal{S}_2]$  with  $\int_{\mathcal{S}_1} p(x) d\mu < 0$ .*

258 *Proof.* Since  $\mathcal{S}_1 \setminus \mathcal{S}_2$  contains an open subset, there exists  $x_0 \in \mathbb{R}^n$  and  $r > 0$   
 259 such that  $\mathcal{S}_1 \setminus \mathcal{S}_2 \supseteq B_r(x_0) =: \{x \in \mathbb{R}^n \mid \|x - x_0\| < r\}$ . Without loss of generality, we  
 260 assume that  $x_0 = 0$ . This can always be guaranteed by applying a simple translation  
 261 to  $\mathcal{S}_1$  and  $\mathcal{S}_2$ . Due to both sets being bounded, there exists an  $R > r$  such that  
 262  $\mathcal{S}_2, \mathcal{S}_1 \subseteq B_R(0)$ .

263 We prove this lemma by constructing a polynomial  $p: \mathbb{R}^n \rightarrow \mathbb{R}$  that is non-  
 264 negative on  $B_R(0) \setminus B_r(0) \supseteq \mathcal{S}_2$  and satisfies  $\int_{B_R(0)} p d\mu < 0$ . If such a  $p$  exists, it  
 265 holds that

$$\begin{aligned} 266 \int_{\mathcal{S}_1} p d\mu &= \int_{\mathcal{S}_1 \setminus B_r(0)} p d\mu + \int_{B_r(0)} p d\mu \\ 267 &\leq \int_{B_R(0) \setminus B_r(0)} p d\mu + \int_{B_r(0)} p d\mu = \int_{B_R(0)} p d\mu < 0. \end{aligned}$$

269 In order to construct  $p$ , let

$$270 \quad q(t) := [c_1(t - c_2)]^2$$

271 be a univariate polynomial with constants  $c_1 := \frac{2}{R^2 - r^2}$ ,  $c_2 := \frac{R^2 + r^2}{2}$ . By construction,  
 272 the following holds:

$$273 \quad (7a) \quad q(c_2) = 0$$

$$274 \quad (7b) \quad q(t^2) = 1 \text{ iff. } t \in \{r, R\},$$

$$275 \quad (7c) \quad q(t^2) \geq 1 \text{ for } t \in [0, r],$$

$$276 \quad (7d) \quad 0 \leq q(t^2) \leq 1 \text{ for } t \in [r, R].$$

278 Taking the  $l$ -th ( $l \in \mathbb{N}$ ) power of  $q$  preserves properties (7a)–(7d). Furthermore, the  
 279 polynomial

$$280 \quad p_l(t) := 1 - q^l(t)$$

281 satisfies

$$282 \quad p_l(c_2) = 1$$

$$283 \quad p_l(t^2) = 0 \text{ iff. } t \in \{r, R\},$$

$$284 \quad p_l(t^2) \leq 0 \text{ for } t \in [0, r],$$

$$285 \quad 0 \leq p_l(t^2) \leq 1 \text{ for } t \in [r, R].$$

287 We now show that there exists  $l \in \mathbb{N}$  such that the radial symmetric polynomial  
 288  $p_l(\|x\|^2)$  is non-negative on  $B_R(0) \setminus B_r(0) \supseteq \mathcal{S}_2$  and satisfies  $\int_{B_R(0)} p_l(\|x\|^2) d\mu < 0$ :

$$\begin{aligned}
 289 \quad \int_{B_R(0)} p_l(\|x\|^2) d\mu &= \int_{B_R(0) \setminus B_r(0)} p_l(\|x\|^2) d\mu + \int_{B_r(0)} p_l(\|x\|^2) d\mu \\
 290 \quad &\leq \int_{B_R(0) \setminus B_r(0)} 1 d\mu + \int_{B_r(0)} 1 - q^l(\|x\|^2) d\mu \\
 291 \quad &= \int_{B_R(0)} 1 d\mu - \int_{B_r(0)} q^l(\|x\|^2) d\mu. \\
 292
 \end{aligned}$$

293 In order to complete the proof, we show that  $\lim_{l \rightarrow \infty} \int_{B_r(0)} q^l(\|x\|^2) d\mu = \infty$ . Using  
 294 a substitution of variables and exploiting the radial symmetry, the integral over the  
 295  $n$ -dimensional ball can be transformed to a univariate integral:

$$296 \quad \int_{B_r(0)} q^l(\|x\|^2) d\mu = n \overbrace{\int_{B_1(0)} 1 d\mu}^{=: \alpha > 0} \int_0^r q^l(t^2) t^{n-1} dt$$

297 Now we calculate the difference between two integrals in the sequence while omitting  
 298 the positive coefficient  $\alpha$ :

$$\begin{aligned}
 299 \quad &\int_0^r q^{l+1}(t^2) t^{n-1} dt - \int_0^r q^l(t^2) t^{n-1} dt \\
 300 \quad &= \int_0^r \overbrace{q^l(t^2)}^{\geq 1} \overbrace{t^{n-1}}^{\geq 0} \overbrace{(q(t^2) - 1)}^{\geq 0} dt \\
 301 \quad &\geq \int_0^r t^{n-1} (q(t^2) - 1) dt = c > 0 \\
 302
 \end{aligned}$$

303 Since the difference between two consecutive elements of the series is bounded from  
 304 below by a strictly positive constant  $c$ , the series diverges to  $+\infty$ . This implies the  
 305 existence of some  $l \in \mathbb{N}$  such that  $\int_{B_R(0)} p_k(\|x\|^2) d\mu < 0$ .  $\square$

306 Using  $p(u) = \sum_{\alpha} p_{\alpha} u^{\alpha}$ , the corresponding optimization problem to certify infea-  
 307 sibility of the robust problem is

$$\begin{aligned}
 308 \quad (\text{PolySepProj}) \quad &\inf_p \sum_{\alpha} p_{\alpha} \int_{\mathcal{U}} u^{\alpha} d\mu, \\
 &p \in \mathcal{P}[\text{Proj}_u(\mathcal{B})].
 \end{aligned}$$

309 Without explicit knowledge of the projection  $\text{Proj}_u(\mathcal{B})$ , it is unclear how the set  
 310  $\mathcal{P}[\text{Proj}_u(\mathcal{B})]$  can be expressed as part of a polynomial optimization problem. We  
 311 present an equivalent model which expresses this constraint by introduction of addi-  
 312 tional linear constraints over the coefficients of the unknown polynomial.

313 **LEMMA 3.2.** *Consider the two polynomial optimization problems*

$$\begin{aligned}
 314 \quad (1) \quad &\inf_p \sum_{\alpha} p_{\alpha} \int_{\mathcal{U}} u^{\alpha} d\mu, & \text{and} & \quad (2) \quad \inf_{\tilde{p}} \sum_{\alpha} \tilde{p}_{\alpha} \int_{\mathcal{U}} u^{\alpha} d\mu, \\
 &p \in \mathcal{P}[\text{Proj}_u(\mathcal{B})], & & \quad \tilde{p}_{\alpha, \beta} = 0 \quad \forall \beta \neq 0, \\
 315 & & & \quad \tilde{p} \in \mathcal{P}[\mathcal{B}].
 \end{aligned}$$



316 *Any feasible point  $p^*$  of (1) can be extended to a feasible point  $\tilde{p}^*$  of (2) and vice versa.*  
 317 *Furthermore, the feasible points  $p^*$  and  $\tilde{p}^*$  have the same objective values.*

318 *Proof.* “ $\Rightarrow$ ”: Let  $p^*$  be any feasible point of (1) with objective value  $z^* =$   
 319  $\sum_{\alpha} p_{\alpha}^* \int_{\mathcal{U}} u^{\alpha} d\mu$ . Consider the inclusion map from  $\mathbb{R}[u]$  to  $\mathbb{R}[u, x]$ , which maps  $p^*$   
 320 to  $\tilde{p}^*$  where  $\tilde{p}^*(u, x) = \sum_{\alpha, \beta} \tilde{p}_{\alpha, \beta}^* u^{\alpha} x^{\beta}$  where

$$321 \quad (8) \quad \tilde{p}_{\alpha, \beta}^* := \begin{cases} p_{\alpha}^*, & \text{if } \beta = 0, \\ 0, & \text{if } \beta \neq 0. \end{cases}$$

322 By construction, for any  $u \in \text{Proj}_u(\mathcal{B})$  and  $x \in \mathbb{R}^{|\mathcal{N}|}$ , we have  $\tilde{p}^*(u, x) = p^*(u) \geq 0$ .  
 323 Therefore  $\tilde{p}^* \in \mathcal{P}[\text{Proj}_u(\mathcal{B}) \times \mathbb{R}^{|\mathcal{N}|}] \subseteq \mathcal{P}[\mathcal{B}]$ . That is  $\tilde{p}^*$  is feasible for (2).

324 “ $\Leftarrow$ ”: Let  $\tilde{p}^*$  be any feasible point of (2). Since all coefficients  $\tilde{p}_{\alpha, \beta}^*$  with  $\beta \neq 0$  are zero,  
 325  $\tilde{p}^*$  is independent of  $x$  and it holds that  $\tilde{p}^* \in \mathcal{P}[\text{Proj}_u(\mathcal{B}) \times \mathbb{R}^{|\mathcal{N}|}]$ . Let  $p^*(u) = \sum_{\alpha} p_{\alpha}^* u^{\alpha}$   
 326 be the remaining polynomial in  $u$ . Together with  $\tilde{p}^* \in \mathcal{P}[\text{Proj}_u(\mathcal{B}) \times \mathbb{R}^{|\mathcal{N}|}]$ , this implies  
 327  $p^* \in \mathcal{P}[\text{Proj}_u(\mathcal{B})]$ .  $\square$

328 For the remainder of this section, we assume that the problem is robust infeasible,  
 329 i.e.  $\mathcal{X} := \mathcal{U} \setminus \text{Proj}_u(\mathcal{B})$  is non-empty. In order to apply [Lemma 3.1](#),  $\mathcal{X}$  has to contain an  
 330 open subset. The next proposition shows that for the given sets, this is no restriction  
 331 since such a subset always exists. Given a set  $\mathcal{S} \subseteq \mathbb{R}^n$ , we denote with  $\text{cl}(\mathcal{S})$ ,  $\text{int}(\mathcal{S})$ ,  
 332  $\partial \mathcal{S}$ , and  $\mathcal{S}^c$  the closure, interior, boundary, and complement of  $\mathcal{S}$ , respectively. For  
 333 this paper, the uncertainty set  $\mathcal{U}$  is assumed to be a full-dimensional hypercube or  
 334 full-dimensional polyhedron. Therefore,  $\mathcal{U} = \text{cl}(\text{int}(\mathcal{U}))$  always holds for our choices  
 335 of  $\mathcal{U}$ .

336 **PROPOSITION 3.3.** *Let  $\mathcal{U} \subseteq \mathbb{R}^{n_1}$  be a set with  $\mathcal{U} = \text{cl}(\text{int}(\mathcal{U}))$ . Let  $\mathcal{B} \subseteq \mathbb{R}^{n_1} \times \mathbb{R}^{n_2}$   
 337 be a compact set and let  $\mathcal{X} = \mathcal{U} \setminus \text{Proj}_u(\mathcal{B}) \neq \emptyset$ . Then  $\mathcal{X}$  contains an open subset.*

338 *Proof.* We need to show that  $\text{int}(\mathcal{X}) = \text{int}(\mathcal{U}) \cap (\text{Proj}_u(\mathcal{B}))^c \neq \emptyset$ . Since  $\mathcal{B}$  is  
 339 compact,  $\text{Proj}_u(\mathcal{B})$  is closed and thus  $(\text{Proj}_u(\mathcal{B}))^c$  is an open set.

340 Pick any  $x \in \mathcal{X} = \mathcal{U} \cap (\text{Proj}_u(\mathcal{B}))^c$ . If  $x \in \text{int}(\mathcal{U})$ , then  $x \in \text{int}(\mathcal{X})$  holds as well  
 341 since  $(\text{Proj}_u(\mathcal{B}))^c$  is an open set.

342 Otherwise, assume that  $x \in \partial \mathcal{U}$ . With  $x \in (\text{Proj}_u(\mathcal{B}))^c$ , there exists  $\varepsilon > 0$  such  
 343 that  $B_{\varepsilon}(x) \subseteq (\text{Proj}_u(\mathcal{B}))^c$ . Since  $\mathcal{U} = \text{cl}(\text{int}(\mathcal{U}))$ , there exists  $y \in \text{int}(\mathcal{U}) \cap B_{\varepsilon}(x) \subseteq$   
 344  $(\text{Proj}_u(\mathcal{B}))^c$ . Therefore,  $y \in \text{int}(\mathcal{X})$ .

345 This concludes that for the given sets,  $\mathcal{X}$  always contains an open subset if  $\mathcal{X}$  is  
 346 non-empty.  $\square$

347 With [Proposition 3.3](#) and [Lemma 3.1](#), the separation problem ([PolySep](#)) can  
 348 certify infeasibility if the assumptions of [Proposition 3.3](#) are satisfied. In practice, this  
 349 optimization problem is then approximated by some finite relaxation of the Lasserre  
 350 hierarchy. The question remains whether for sufficiently large levels of the hierarchy,  
 351 the separation polynomial as given by [Lemma 3.1](#) can always be found. After all, not  
 352 all positive polynomials can be expressed by sum of square polynomials. This is no  
 353 restriction as the following proposition shows:

354 **PROPOSITION 3.4.** *There is some finite level of the Lasserre hierarchy for which  
 355 the corresponding SDP approximation of ([PolySep](#)) yields a negative objective if  $\mathcal{X} \neq$   
 356  $\emptyset$ .*

357 *Proof.* By [Proposition 3.3](#),  $\mathcal{X} \neq \emptyset$  implies the existence of some open subset in  
 358  $\mathcal{X}$ . Then [Lemma 3.1](#) guarantees the existence of a polynomial  $p$  with strictly negative

359 objective value for the abstract polynomial optimization problem.

360 Consider then the SDP approximation of (PolySep). Since SOS-polynomials are dense  
 361 (see [15]) in the set of non-negative polynomials and by the continuity of the integral,  
 362 there is always a SOS-polynomial close to the  $p$  with a negative objective value.  $\square$

363 **3.2. A Set Containment Approach for Certifying Feasibility.** For certi-  
 364 fying robust feasibility, we need the following assumption:

365 ASSUMPTION 3.5. *Assume that there is a function  $g: \mathcal{U} \rightarrow \mathbb{R}^{n_2}$  such that  $\mathcal{G}_{\mathcal{U}} =$   
 366  $\{u, x \mid u \in \mathcal{U}, x = g(u)\}$ .*

367 In general, the task that has to be solved in order to decide robust feasibility is to  
 368 check whether

$$369 \quad \mathcal{U} \subseteq \text{Proj}_{\phi}(\mathcal{B}).$$

370 Since an explicit description of  $\text{Proj}_{\phi}(\mathcal{B})$  is typically not available, a different approach  
 371 is used in this section. The basic idea is to replace the original set containment problem  
 372 with an equivalent set containment problem

$$373 \quad \mathcal{G}_{\mathcal{U}} \subseteq \mathcal{H},$$

374 where  $\mathcal{H} = \{x \in \mathbb{R}^n \mid h_1(x) \geq 0, \dots, h_m(x) \geq 0\}$  is constructed by (possibly nonlinear)  
 375 functions  $h_i$ . This set containment problem can then be decided using the optimiza-  
 376 tion problems

$$377 \quad (\text{MinCons}) \quad \inf_{x \in \mathcal{G}_{\mathcal{U}}} h_i(x) \quad i = 1, \dots, m.$$

378 The optimal solution of all  $m$  optimization problems exists and is the objective value  
 379 is non-negative if and only if  $\mathcal{G}_{\mathcal{U}} \subseteq \mathcal{H}$ . In cases where global optimality cannot be  
 380 obtained easily, the criterion can be weakened by replacing the optimization problems  
 381 (MinCons) with relaxations: non-negative objective values of the relaxations imply  
 382 non-negative objective values of the original problems. However, this is only a suf-  
 383 ficient criterion since  $\mathcal{G} \subseteq \mathcal{H}$  might hold but at the same time some optimization  
 384 problems might obtain negative objective values only due to the relaxation.

385 LEMMA 3.6. *Let  $\mathcal{U} \subseteq \mathbb{R}^{n_1}$ . Let  $g: \mathcal{U} \rightarrow \mathbb{R}^{n_2}$  be a function such that Assump-  
 386 tion 3.5 is satisfied and let  $h_i: \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \rightarrow \mathbb{R}$  ( $n_1, n_2 \in \mathbb{N}$ ) for  $i = 1, \dots, m$  be  
 387 functions. Let*

$$388 \quad \mathcal{G}_{\mathcal{U}} := \{(u, x) \in \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \mid u \in \mathcal{U}, x = g(u)\},$$

$$389 \quad \mathcal{H} := \{(u, x) \in \mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \mid h_i(u, x) \geq 0, i = 1, \dots, m\}$$

390 with

$$391 \quad \mathcal{B} := \mathcal{G}_{\mathcal{U}} \cap \mathcal{H}.$$

392 Then

$$393 \quad \mathcal{U} \subseteq \text{Proj}_u(\mathcal{B}) \iff \mathcal{G}_{\mathcal{U}} \subseteq \mathcal{H}.$$

394 *Proof.* “ $\Rightarrow$ ”: Suppose  $\mathcal{U} \subseteq \text{Proj}_u(\mathcal{B})$ . Pick any  $(u, x) \in \mathcal{G}_{\mathcal{U}}$ . Due to the projection,  
 395 there exists  $x'$  with  $(u, x') \in \mathcal{B} = \mathcal{G}_{\mathcal{U}} \cap \mathcal{H}$ . As Assumption 3.5 is satisfied,  $x$  is uniquely  
 396 determined for any  $u \in \mathcal{U}$ . Therefore  $x = x' = g(u)$  holds and thus  $(u, x) \in \mathcal{H}$ .

397 “ $\Leftarrow$ ”: Suppose  $\mathcal{G}_{\mathcal{U}} \subseteq \mathcal{H}$ . Pick any  $u \in \mathcal{U}$  and let  $x = g(u)$ . Then  $(u, x) \in \mathcal{G}_{\mathcal{U}} \subseteq \mathcal{H}$   
 398 and thus  $(u, x) \in \mathcal{B}$ . This implies  $u \in \text{Proj}_u(\mathcal{B})$ .  $\square$

400 This lemma can be applied to all problems where a subset of the constraints defines  
 401 a unique solution for each possible realization of the data. Even if  $g$  is only given  
 402 implicitly by the solution of some (in-)equality system, the lemma is still applicable.

403 The next lemma shows how the set containment question can still be decided if  
 404 the considered sets are partitioned into subsets. This will be important later when  
 405 eliminating the absolute values of the gas transport problem.

406 **LEMMA 3.7.** *Let  $\mathcal{U} \subseteq \mathbb{R}^{n_1}$  and let  $A_{\mathcal{U}}, B \subseteq \mathbb{R}^{n_1} \times \mathbb{R}^{n_2}$  with  $A_{\mathcal{U}} = \{(u, x) \in$   
 407  $\mathbb{R}^{n_1} \times \mathbb{R}^{n_2} \mid x = g(u), u \in \mathcal{U}\}$  for an arbitrary function  $g: \mathbb{R}^{n_1} \rightarrow \mathbb{R}^{n_2}$ . Let  $S_i$  ( $i \in I$ )  
 408 be a collection of sets with  $S_i \subseteq \mathbb{R}^{n_1} \times \mathbb{R}^{n_2}$  such that  $\bigcup_{i \in I} S_i = \mathbb{R}^{n_1} \times \mathbb{R}^{n_2}$ . Then*

$$\begin{aligned} 409 \quad U &= \text{Proj}_u(A_{\mathcal{U}}) \subseteq \text{Proj}_u(A_{\mathcal{U}} \cap B) \\ 410 \quad &\iff \\ 411 \quad \text{Proj}_u(A_{\mathcal{U}} \cap S_i) &\subseteq \text{Proj}_u(A_{\mathcal{U}} \cap S_i \cap B) \quad \forall i \in I \end{aligned}$$

*Proof.*

$$\begin{aligned} 413 \quad U &= \text{Proj}_u(A_{\mathcal{U}}) \subseteq \text{Proj}_u(A_{\mathcal{U}} \cap B) \\ 414 \quad &\stackrel{\text{Lemma 3.6}}{\iff} A_{\mathcal{U}} \subseteq B \iff A_{\mathcal{U}} \cap S_i \subseteq B \cap S_i \quad (\forall i \in I) \end{aligned}$$

416 Let  $\mathcal{U}'_i := \text{Proj}_u(A_{\mathcal{U}} \cap S_i)$ . Rewriting  $A_{\mathcal{U}} \cap S_i$  yields

$$\begin{aligned} 417 \quad A_{\mathcal{U}} \cap S_i &= \{(u, x) \mid x = g(u), u \in \mathcal{U}, (u, x) \in S_i\} \\ 418 \quad &= \{(u, x) \mid x = g(u), u \in \mathcal{U}, (u, g(u)) \in S_i\} \\ 419 \quad &= \{(u, x) \mid x = g(u), u \in \{u \mid u \in \mathcal{U}, (u, g(u)) \in S_i\}\} \\ 420 \quad &= \{(u, x) \mid x = g(u), u \in \text{Proj}_u(A_{\mathcal{U}} \cap S_i)\} \\ 421 \quad &= A_{\text{Proj}_u(A_{\mathcal{U}} \cap S_i)} = A'_{\mathcal{U}'_i}. \end{aligned}$$

423 Then

$$\begin{aligned} 424 \quad A_{\mathcal{U}} \cap S_i &= A'_{\mathcal{U}'_i} \subseteq B \cap S_i \quad (\forall i \in I) \\ 425 \quad &\stackrel{\text{Lemma 3.6}}{\iff} \mathcal{U}'_i = \text{Proj}_u(A'_{\mathcal{U}'_i}) \subseteq \text{Proj}_u(A'_{\mathcal{U}'_i} \cap B) = \text{Proj}_u(A_{\mathcal{U}} \cap B \cap S_i) \quad (\forall i \in I). \quad \square \end{aligned}$$

427 For a practical application, the optimization problems (**MinCons**) need to be  
 428 solved to global optimality. As mentioned earlier, if global optimality cannot be  
 429 ensured, a relaxation of the given problem can also suffice. The structure of the opti-  
 430 mization problems depends on the defining functions of  $\mathcal{G}_{\mathcal{U}}, \mathcal{H}$ . For the gas network  
 431 problem, these typically are polynomials or piecewise polynomials. Using the ideas  
 432 of [subsection 4.3](#), the piecewise polynomial functions can be reformulation in terms  
 433 of pure polynomials. Instead of solving the resulting polynomial optimization prob-  
 434 lems (**MinCons**), sum of squares or moment relaxation of these problems are used  
 435 instead. These relaxations form a hierarchy of semidefinite programs, see [\[21\]](#) and  
 436 [\[14\]](#), respectively.

437 **4. Deciding Robustness for the Passive Gas Network Problem.** In this  
 438 section, the passive gas network problem under uncertainty is introduced. It also  
 439 contains crucial properties of the problem class as well as techniques for reduction of  
 440 variables and procedures to eliminate the occurring absolute value functions. Com-  
 441 bined, these ideas allow a compact problem formulation as a polynomial feasibility  
 442 system which will can be tackled using methods from [section 3](#).

443 **4.1. The Passive Gas Network Problem.** We consider a stationary passive  
 444 gas network with horizontal pipes. Gas can be inserted or withdrawn at each node of  
 445 the network. The goal is to decide whether a given set of demands can be satisfied  
 446 by the network. Even in the absence of uncertainties, this problem is challenging to  
 447 solve since the resulting feasibility problem is in general nonlinear, non-smooth and  
 448 non-convex.

449 **4.1.1. Modeling the Nominal Passive Gas Network Feasibility Problem.**

450 The network's topology is given by a weakly connected digraph  $G = (V^+, A)$  with  
 451  $|V^+| = |\{0, \dots, n+1\}| = n+1$  nodes and  $|A| = m \geq n$  arcs. The physical state  
 452 of the network is represented by the (non-negative) pressure  $p_v \in \mathbb{R}_{\geq 0}$  at each node  
 453  $v \in V$  and the flow  $q_a \in \mathbb{R}$  along each arc  $a \in A$ . Concerning the flow, a positive  
 454 sign of  $q_a$  indicates flow in edge direction, a negative sign the reverse. Since the  
 455 pressure only occurs in squared form, we introduce variables  $p_v^2 = \pi_v \in \mathbb{R}_{\geq 0}$  for the  
 456 squared pressures, see (10). Due to physical, technical and legal reasons, the squared  
 457 pressures are bounded:  $\pi_v \in [\underline{\pi}_v, \bar{\pi}_v]$ ,  $v \in V^+$ . For a more comprehensive treatment  
 458 of the gas transport problem, see e.g. [1]. A general survey on the problems arising  
 459 in gas network operations is given in [24].

460 Gas networks share a basic property with linear flow networks: at each node, flow  
 461 conservation must hold. Similar to the linear case, gas may be inserted or withdrawn  
 462 at each node of the network. This so called demand or *nomination* is encoded in the  
 463 vector  $(q_v^{\text{nom}})_{v \in V^+}$  which has to be balanced:  $\sum_{v \in V^+} q_v^{\text{nom}} = 0$ . Insertion is indicated  
 464 by a positive sign, withdrawal by a negative sign of  $q_v^{\text{nom}}$ . Flow conservation can then  
 465 be stated as

466 (9) 
$$\sum_{a=(v,w) \in A} q_a - \sum_{a=(w,v) \in A} q_a = q_v^{\text{nom}}, \quad \forall v \in V^+.$$

467 So far, the model is identical to a regular linear network flow problem. More com-  
 468 plexity in the form of nonlinear constraints is introduced once the physical laws of gas  
 469 transport are considered.

470 According to the Weymouth Equation (10) (see [29]), when gas flows through a  
 471 pipe, its pressure decreases. The difference of the squared pressures at both ends of  
 472 the pipe is proportional to the signed squared flow along the pipe. The magnitude of  
 473 the pressure drop is influenced by the pipe's pressure loss factor  $\phi_a$ , which (amongst  
 474 other factors) depends upon the length, diameter and roughness of the pipe. A more  
 475 in depth look at the different modeling approaches for the pressure loss factor can be  
 476 found in [1] and [22].

477 By defining  $f(x) := x|x|$ , the pressure loss relation can be expressed as

478 (10) 
$$\pi_v - \pi_w = \phi_a |q_a| q_a = \phi_a f(q_a), \quad \forall a = (v, w) \in A.$$

479 Let  $\mathcal{A}^+ \in \mathbb{R}^{|V^+| \times |A|}$  be the node-arc-incidence matrix of  $G$ , that is  $(\mathcal{A}^+)_{av} = +1$   
 480 and  $(\mathcal{A}^+)_{aw} = -1$  for  $a = (v, w) \in A$ . With  $\mathcal{A}^+$ , the flow conservation (9) can be  
 481 stated in a more compact manner:

482 (11) 
$$\mathcal{A}^+ q = q^{\text{nom}+}.$$

483 By defining  $\Phi(\phi) := \text{diag}(\phi_1, \dots, \phi_{|A|})$  and  $F(q) := ((f(q_1), \dots, f(q_{|A|}))^T$ , the pres-  
 484 sure loss constraints (10) can be combined to

485 (12) 
$$\mathcal{A}^{+T} \pi = -\Phi(\phi) F(q).$$

486 With (11) and (12), the feasibility problem can be stated as a potential driven network  
487 problem

$$\begin{aligned} & \mathcal{A}^+ q = q^{\text{nom}+}, \\ & \mathcal{A}^{+T} \pi = -\Phi(\phi)F(q), \\ & \pi \in [\underline{\pi}, \bar{\pi}], \\ & q \in \mathbb{R}^{|A|}. \end{aligned} \tag{PotN}$$

489 **4.1.2. Reduction of Variables.** By a result of [8], all pressure variables and  
490  $|V^+| - 1$  of the flow variables can be eliminated from the system. It is well known that  
491 for connected graphs,  $\mathcal{A}^+$  has rank  $|V^+| - 1$  and an arbitrary row can be removed  
492 while preserving the set of solutions of (9). For ease of notation, we discard the row  
493 corresponding to node 0 and obtain  $\mathcal{A}$  from  $\mathcal{A}^+$  in this way. The set  $V = V^+ \setminus \{0\} =$   
494  $\{1, \dots, n\}$  of nodes and the demand vector  $q^{\text{nom}+}$  are adjusted accordingly.

495 **THEOREM 4.1** ([8]). *Let  $\mathcal{A}$  be the node-arc-incidence-matrix of a graph  $G$  as de-*  
496 *scribed above and let  $\mathcal{A} = (\mathcal{A}_B, \mathcal{A}_N)$  be partition into basis and non basis submatrices*  
497 *of  $\mathcal{A}$ . Let  $(\Phi_B(\phi), \Phi_N(\phi))$ ,  $(F_B, F_N)$ , and  $(q_B, q_N)$  be the corresponding partitions*  
498 *of  $\Phi(\phi)$ ,  $F$ , and  $q$ , respectively. Define*

$$499 \quad g: \mathbb{R}^{|A|} \times \mathbb{R}^{|N|} \rightarrow \mathbb{R}^{|V|}, \quad g(\phi_B, q_N) := (\mathcal{A}_B^T)^{-1} \Phi_B(\phi) F_B (\mathcal{A}_B^{-1} (q^{\text{nom}} - \mathcal{A}_N q_N)).$$

500 *Then the model (PotN) is equivalent to the following reduced model in variables*  
501  *$q_N$ :*

$$\begin{aligned} & \mathcal{A}_N^T g(\phi, q_N) = \Phi_N(\phi) F_N(q_N) \\ & \underline{\pi}_0 \leq \min_{i=1, \dots, n} [\bar{\pi}_i + g_i(\phi, q_N)] \\ & \bar{\pi}_0 \geq \max_{i=1, \dots, n} [\underline{\pi}_i + g_i(\phi, q_N)] \\ & \min_{i=1, \dots, n} [\bar{\pi}_i + g_i(\phi, q_N)] \geq \max_{i=1, \dots, n} [\underline{\pi}_i + g_i(\phi, q_N)] \\ & q_N \in \mathbb{R}^{|N|}, \end{aligned} \tag{RPotN}$$

503 *where  $\underline{\pi}_0, \bar{\pi}_0$  are the squared pressure bounds at the root node, respectively.*

504 *If a feasible  $q_N$  for (RPotN) exists, the remaining variables  $q_B, \pi$  can be recovered*  
505 *through  $q_B = \mathcal{A}_B^{-1} (q^{\text{nom}} - \mathcal{A}_N q_N)$  and  $\pi_i = \pi_0 - g_i(\phi, q_N)$  ( $i = 1, \dots, n$ ). The value*  
506 *of  $\pi_0$  is an arbitrary given element of*

$$507 \quad \left[ \max_{i=1, \dots, n} [\underline{\pi}_i + g_i(\phi, q_N)], \min_{i=1, \dots, n} [\bar{\pi}_i + g_i(\phi, q_N)] \right].$$

508 *Conversely, a vector  $q_N$  that was extracted from a solution  $q^*, \pi^*$  of (PotN) is feasible*  
509 *for (RPotN).*

510 Depending on the situation, it can be beneficial to consider the reduced problem  
511 (RPotN) or the original problem (PotN). For that purpose, let

$$\begin{aligned} & q: \mathbb{R}^{|N|} \rightarrow \mathbb{R}^{|A|}, \\ & q_a(q_N) := \begin{cases} (\mathcal{A}_B^{-1} (q^{\text{nom}} - \mathcal{A}_N q_N))_a, & \text{if } a \in B, \\ (q_N)_a, & \text{if } a \in N. \end{cases} \end{aligned}$$

515 This affine linear function maps cycle flow values to flows on all arcs of the graph. For  
516 graphs with a single cycle,  $q$  can be simplified to  $q_a(q_N) = q_N - \beta_a$  for some  $\beta_a \in \mathbb{R}$ .

517 **4.1.3. Uniqueness of Flow.** Another important result in this context concerns  
 518 the structure of the feasible set of (PotN). As shown in [5, 25], the feasible flow of a  
 519 given demand scenario for a network without pressure bounds is uniquely determined.

520 THEOREM 4.2 ([5]). *Consider (PotN) without pressure bounds. Then for fixed*  
 521  $\phi \in \mathbb{R}_{>0}^{|A|}$ , *the solution space has the following properties:*

- 522 1. *The projection on the flow variable  $q$  contains a single point, i.e. the flow is*  
 523 *unique.*
- 524 2. *The projection on the squared pressure variable  $\pi$  has the form*

$$525 \quad \left\{ \pi^* + \eta(1, \dots, 1)^T \mid \eta \in \mathbb{R} \right\}.$$

526 In case of pressure bounds, the variable  $\eta$  is constrained:

$$527 \quad \eta \in [\underline{\eta}, \bar{\eta}] \quad \text{with} \quad \underline{\eta} := \max_{v \in V} (\underline{\pi}_v - \pi_v^*) \quad \text{and} \quad \bar{\eta} := \min_{v \in V} (\bar{\pi}_v - \pi_v^*).$$

529 As a simple consequence, if the pressure of a feasible problem is fixed at any node,  
 530 the pressure values at the remaining network nodes are also uniquely determined.

531 **4.1.4. The Passive Gas Network Problem Under Uncertainty.** Based on  
 532 this nominal setting (PotN) and (RPotN), uncertainty is introduced into the prob-  
 533 lem. Disregarding any combinatorial uncertainties (e.g. random failing of arcs), two  
 534 possible sources of uncertainty are present in the given model: fluctuations in the  
 535 demand  $q_v^{\text{nom}}$  and variations of the pressure loss factor  $\phi_a$ . In this paper, we focus  
 536 on uncertainties in the pressure loss coefficient. The value of  $\phi_a$  is influenced by spe-  
 537 cific chemical properties of the gas as well as physical parameters of the pipe like e.g.  
 538 its length, diameter and roughness. In particular, the roughness value of the pipe's  
 539 wall changes during the network's operation due to aging effects and accumulation  
 540 of dirt. It is difficult to measure this parameter after the network begins operation.  
 541 Since the roughness values can only be estimated, a robust treatment of the prob-  
 542 lem is reasonable. The goal of robust optimization is to immunize solutions of an  
 543 optimization problem against a set of parameters which can be realized from a given  
 544 uncertainty set. The problem is required to be solvable for all possible realization of  
 545 the uncertainty.

546 It is assumed that the pressure loss factor of each pipe is strictly positive and lies  
 547 within some a-priori known interval

$$548 \quad \phi_a \in [\underline{\phi}_a, \bar{\phi}_a] \subseteq \mathbb{R}_{>0} \quad \forall a \in A$$

549 with  $0 < \underline{\phi}_a \leq \bar{\phi}_a$ . Furthermore, possible correlation between different pipes is  
 550 ignored. The resulting uncertainty set  $\mathcal{U}$  is therefore given by the hyperrectangle

$$551 \quad \mathcal{U} := \times_{a \in A} [\underline{\phi}_a, \bar{\phi}_a].$$

553 By Theorem 4.2, a problem without pressure bounds always admits a uniquely  
 554 determined flow that satisfies the given demand. Parameterizing this result by the  
 555 pressure loss factors motivates the following corollary:

556 COROLLARY 4.3. *For networks without pressure bounds, there exists a function*

$$557 \quad \tilde{q}: \mathbb{R}_{>0}^{|A|} \rightarrow \mathbb{R}^{|N|}$$

$$558 \quad \phi \mapsto \tilde{q}(\phi)$$

560 that solves

$$561 \quad \mathcal{A}_N^T g(\phi, \tilde{q}(\phi)) = \Phi_N(\phi) F_N(\tilde{q}(\phi))$$

562 for all  $\phi \in \mathbb{R}_{>0}^{|A|}$ .

563 **4.1.5. Deciding Robustness of the Gas Network Problem.** Using model  
564 (RPotN), let

$$565 \quad \mathcal{G} := \left\{ (\phi, q_N) \in \mathbb{R}_{>0}^{|A|} \times \mathbb{R}^{|N|} \mid \mathcal{A}_N^T g(\phi, q_N) - \Phi_N(\phi) F(q_N) = 0 \right\},$$

$$566 \quad \mathcal{G}_{\mathcal{U}} := \{ (\phi, q_N) \in \mathcal{G} \mid \phi \in \mathcal{U} \}$$

567 and

$$569 \quad \mathcal{H} := \left\{ (\phi, q_N) \left| \begin{array}{ll} -\underline{\pi}_0 + \bar{\pi}_i + g_i(\phi_B, q_N) \geq 0, & i \in \{1, \dots, n\} \\ \bar{\pi}_0 - \underline{\pi}_i - g_i(\phi_B, q_N) \geq 0, & i \in \{1, \dots, n\} \\ \bar{\pi}_i + g_i(\phi_B, q_N) - \underline{\pi}_j - g_j(\phi_B, q_N) \geq 0, & i, j \in \{1, \dots, n\} \\ (\phi, q_N) \in \mathbb{R}_{>0}^{|A|} \times \mathbb{R}^{|N|} \end{array} \right. \right\}.$$

571 The set  $\mathcal{G}$  (resp.  $\mathcal{G}_{\mathcal{U}}$ ) contains all feasible combinations  $\phi, q_N$  (resp. with  $\phi \in \mathcal{U}$ ) arising  
572 from the cycle flow equations. Due to [Corollary 4.3](#), this set can be stated equivalently  
573 as the graph of  $g(\phi)$ . On the other hand,  $\mathcal{H}$  can be seen as all combinations  $\phi, q_N$   
574 that are feasible for the given pressure bounds.

575 Combining both  $\mathcal{G}$  and  $\mathcal{H}$ , let

$$576 \quad \mathcal{B} := \mathcal{G} \cap \mathcal{H}$$

577 be the set of all feasible uncertainty/solution pairs of the given gas transport problem.

578 The task is now to decide whether the network allows a feasible flow for all  $\phi \in \mathcal{U}$ .  
579 Let  $\text{Proj}_{\phi}(\mathcal{B})$  be the projection of the feasible pairs of pressure loss coefficients and  
580 flows onto the space of the uncertainty set. This set contains all pressure loss coef-  
581 ficients which admit a feasible flow in the corresponding problem. In this context,  
582 deciding robustness with respect to  $\mathcal{U}$  is equivalent to checking whether the uncer-  
583 tainty set  $\mathcal{U}$  is contained in the projection  $\text{Proj}_{\phi}(\mathcal{B})$ :

$$584 \quad \mathcal{U} \subseteq \text{Proj}_{\phi}(\mathcal{B}) = \{ \phi \mid \exists q_N : (\phi, q_N) \in \mathcal{B} \}.$$

585 **4.2. Deciding Robust Feasibility on Tree Networks.** Consider a network  
586 whose underlying topology is a tree, i.e. a connected, cycle-free graph. Since there are  
587 no cycles and therefore  $N = \emptyset$ , the description of the feasible set  $\mathcal{B}$  does not contain  
588 any cycle flow variables  $q_N$ . Since there are no flow variables, the function  $g(\phi, q_N)$   
589 as defined in [Theorem 4.1](#) is reduced to a function of the form

$$590 \quad g(\phi) = (\mathcal{A}_B^T)^{-1} \Phi_B(\phi) F_B(\mathcal{A}_B^{-1} q^{\text{nom}}).$$

591 From this description, we can see that  $g(\phi)$  is a linear function of  $\phi$ . Note that  
592  $F_B(\mathcal{A}_B^{-1} q^{\text{nom}})$  is a constant expression that can be calculated in advance.

593 With  $N = \emptyset$ , the set

$$594 \quad (13) \quad \mathcal{B} = \left\{ \phi \in \mathbb{R}_{\geq 0}^{|A|} \left| \begin{array}{l} \underline{\pi}_0 \leq \min_{i=1, \dots, n} [\bar{\pi}_i + g_i(\phi)] \\ \bar{\pi}_0 \geq \max_{i=1, \dots, n} [\underline{\pi}_i + g_i(\phi)] \\ \min_{i=1, \dots, n} [\bar{\pi}_i + g_i(\phi)] \geq \max_{i=1, \dots, n} [\underline{\pi}_i + g_i(\phi)] \end{array} \right. \right\}$$

595 is polyhedral since all  $g_i(\phi)$  are linear and the min / max expressions can be replaced  
596 by a finite number of linear constraints.

597 In this case, checking robust feasibility with respect to a given polyhedral uncer-  
598 tainty set  $\mathcal{U}$  is equivalent to deciding the set containment problem

$$599 \quad \mathcal{U} \subseteq \text{Proj}_\phi(\mathcal{B}) = \mathcal{B}$$

600 for two polyhedra  $\mathcal{U}$  and  $\mathcal{B}$ . As the following lemma by [17] shows, this can be done  
601 efficiently with LP duality:

602 LEMMA 4.4 ([17]). *Let the set  $\mathcal{S}_1 := \{x \mid Sx \geq s\}$  and let  $\mathcal{S}_2 := \{x \mid Tx \leq t\}$ ,  
603 where  $S \in \mathbb{R}^{m \times n}$ ,  $T \in \mathbb{R}^{k \times n}$  and let  $T$  be nonempty. Then the following are equiva-  
604 lent:*

605 1.  $\mathcal{S}_2 \subseteq \mathcal{S}_1$ , that is:

$$606 \quad Tx \leq t \implies Sx \geq s.$$

607 2. For  $i = 1, \dots, m$ , the  $m$  linear programs are solvable and satisfy:

$$608 \quad \min_x \{(Sx)_i \mid Tx \leq t\} \geq s_i.$$

609 3. There exists a matrix  $W \in \mathbb{R}^{m \times k}$  such that:

$$610 \quad S + WT = 0, \quad s + Wt \leq 0, \quad W \geq 0.$$

611 *Proof.* See [17]. □

612 COROLLARY 4.5. *Let  $\mathcal{U} = \{\phi \mid T\phi \leq t\}$  be a polyhedral uncertainty set. Let  $\mathcal{B} =$   
613  $\{\phi \mid S\phi \geq s\}$  be the polyhedral set of feasible pressure loss factors  $\phi$  for a gas transport  
614 problem over a tree-shaped network.*

615 *Then robustness with respect to  $\mathcal{U}$  can be decided by solving a linear program.*

616 **4.2.1. Robust Feasibility of Tree Networks as a Function of a Node's**  
617 **Pressure.** Corollary 4.5 allows us to characterize robustness of a tree network in  
618 terms of the pressure at an arbitrary chosen node. Let  $G = (V, A)$  be the graph of a  
619 tree network. Without loss of generality, we select the tree's root node 0 as basis of our  
620 considerations. Suppose the pressure value at this node is fixed, i.e.  $\pi_0 := \underline{\pi}_0 = \bar{\pi}_0$ .  
621 Our aim is to specify all  $\pi_0$  such that the gas network problem is robust feasible.

622 As can be inferred from (13), the pressure bounds only appear as constants in the  
623 linear inequality constraints. With the conventions of the previous corollary, the set  
624 of feasible pressure loss coefficients can thus be expressed in terms of the root node's  
625 pressure  $\pi_0$ :

$$626 \quad \mathcal{B}(\pi_0) = \{\phi \mid S\phi \geq s(\pi_0)\}.$$

627 The right hand side  $s$  of the linear inequality system is a linear function  $s: \mathbb{R} \rightarrow \mathbb{R}^{|A|}$   
628 of  $\pi_0$ . Applying Lemma 4.4 to the set containment question  $\mathcal{U} \subseteq \mathcal{B}(\pi_0)$  yields

$$629 \quad \mathcal{U} = \{\phi \mid T\phi \leq t\} \subseteq \{\phi \mid S\phi \geq s(\pi_0)\} = \mathcal{B}(\pi_0)$$

$$630 \quad \iff \mathcal{X}(\pi_0) := \left\{ W \in \mathbb{R}_{\geq 0}^{m \times k} \mid \begin{array}{l} S + WT = 0 \\ s(\pi_0) + Wt \leq 0 \end{array} \right\} \neq \emptyset.$$

631



632 LEMMA 4.6. *Given a tree network  $G = (V, A)$  with an arbitrary root node  $0$  and*  
 633 *a polyhedral uncertainty set  $\mathcal{U}$ . Then the network is robust feasible if and only if the*  
 634 *root node's squared pressure satisfies*

$$635 \quad \pi_0 \in [\underline{\pi}_0^*, \bar{\pi}_0^*]$$

636 *with  $\underline{\pi}_0^*, \bar{\pi}_0^*$  being optimal values of the linear programs*

$$637 \quad (14a) \quad \underline{\pi}_0^* := \min_{\pi_0, W} \pi_0 \text{ s.t. } W \in \mathcal{X}(\pi_0),$$

$$638 \quad (14b) \quad \bar{\pi}_0^* := \max_{\pi_0, W} \pi_0 \text{ s.t. } W \in \mathcal{X}(\pi_0).$$

640

641 *Proof.* The set  $\{(\pi_0, W) \mid W \in \mathcal{X}(\pi_0)\}$  is polyhedral and thus convex. Therefore,  
 642 the set of all feasible  $\pi_0$  is the interval

$$643 \quad [\underline{\pi}_0^*, \bar{\pi}_0^*]$$

644 whose endpoints are the optimal values of the linear programs (14a) and (14b).  $\square$

645 **4.3. Eliminating the Absolute Value Functions.** In order to apply tools  
 646 from polynomial optimization to the gas network problem, the constraining functions  
 647 of  $\mathcal{B}$  have to be converted to a polynomial representation. Currently, the pressure  
 648 drop equations

$$649 \quad \pi_v - \pi_w = \phi q_a |q_a| = \phi f(q_a)$$

650 introduce absolute values in the problem. After elimination of the absolute values,  $\mathcal{B}$   
 651 is transformed from a piecewise polynomial representation to an equivalent but purely  
 652 polynomial description. Depending on the topology of a given instance, it may be  
 653 possible to eliminate a lot of absolute values in advance since all arcs which are not  
 654 part of a cycle have fixed flow direction. For example, in the case of tree networks, all  
 655 directions are known in advance. Apart from that, the flow direction can be fixed by  
 656 other preprocessing algorithms, e.g., flow/pressure propagation or bound tightening  
 657 methods. Further discussion on that topic can be found in [7].

658 This chapter presents three different methods for the elimination of absolute val-  
 659 ues. First, a technique from mixed-integer optimization is employed to model absolute  
 660 values using binary variables. With this method, both the feasibility and the infeas-  
 661 ibility method can be used. Next, the implications of straight forward case distinction  
 662 are discussed. In general, this technique can only be used for the feasibility method  
 663 as will be later explained. Finally, the case distinction idea is further investigated  
 664 for networks which contain a single cycle. In this setting, the absolute values can be  
 665 eliminated by restricting the uncertainty set to polyhedral subsets. It is shown how  
 666 the overall problem can be decomposed into linearly many subproblems which can be  
 667 decided with both methods.

668 **4.3.1. Elimination by Auxiliary Binary Variables.** By introducing addi-  
 669 tional binary variables, the absolute value functions can be eliminated. This technique  
 670 is very similar to what is typically done in mixed-integer optimization. We demon-  
 671 strate the idea using the example of  $|x|x$ . Assume that  $|x|$  is bounded:  $|x| \leq M$ . This  
 672 is a natural assumption since the flows within the network cannot become arbitrary

673 large. With the introduction of a new binary variable  $b$ , the signed-square expression  
 674  $y = |x|x$  can be stated equivalently using polynomials via

$$\begin{aligned} 675 \quad & y = (2b - 1)x^2, \\ 676 \quad & (-1 + b)M \leq x \leq bM, \\ 677 \quad & b = b^2. \end{aligned}$$

679 Applying this construction to each absolute value function on each arc  $a \in A$  yields a  
 680 purely polynomial description of  $\mathcal{B}$  that can be used in the feasibility and infeasibility  
 681 methods.

682 **4.3.2. Elimination by Case Distinction: the General Case.** Using the  
 683 original problem definition (PotN), each pipe  $a \in A$  introduces an absolute value  
 684 with its pressure loss equation. In general, one might expect that by eliminating each  
 685 absolute value function, the problem is split into  $2^{|A|}$  cases. This paragraph shows  
 686 how the number of cases mainly depends on the amount of fundamental cycles in the  
 687 graph and thus can be much smaller than  $2^{|A|}$ . We remark that the following results  
 688 identify the feasible flow directions in a linear network flow model instead of the gas  
 689 transport problem. However, this is no restriction since adding constraints concerning  
 690 the gas physics reduces the number of possible cases even further.

691 Due to Lemma 3.7, the overall set containment problem can be decided by split-  
 692 ting the problem into a series of subproblems. Each subproblem arises by restricting  
 693 the original problem to certain subsets, e.g., to orthants of  $\mathbb{R}^{|A|}$  for the absolute value  
 694 case distinction. Let  $O_1, \dots, O_{2^{|A|}} = \{\mathbb{R}_{\geq 0}, \mathbb{R}_{\leq 0}\}^{|A|}$  be the set of orthants in  $\mathbb{R}^{|A|}$ . In  
 695 the original model (PotN), the additional constraint  $q \in O_i$  restricts the flow to a spe-  
 696 cific orthant and allows the elimination of all absolute value functions. In the reduced  
 697 model, the variables  $q_B$  are replaced by  $q_B = \mathcal{A}_B^{-1}(q^{\text{nom}} - \mathcal{A}_N q_N)$ . The transformed  
 698 case distinction is

$$699 \quad \begin{pmatrix} q_B \\ q_N \end{pmatrix} = \begin{pmatrix} \mathcal{A}_B^{-1}(q^{\text{nom}} - \mathcal{A}_N q_N) \\ q_N \end{pmatrix} \in O_i.$$

700 By considering the reduced model, the next proposition shows that the number of  
 701 case distinctions mainly depends on the amount of fundamental cycles in the graph.

702 **PROPOSITION 4.7.** *Let  $G$  be a connected digraph with  $|A|$  arcs and  $|N|$  funda-*  
 703 *mental cycles. Then there can be at most  $\sum_{i=0}^{|N|} \binom{|A|}{i} \in \mathcal{O}(|A|^{|N|})$  many feasible flow*  
 704 *directions in the network. The corresponding subproblems can be constructed in run*  
 705 *time  $\mathcal{O}(|A|^{|N|})$ .*

706 *Proof.* The problem of finding all feasible flow directions can be reduced to a  
 707 problem concerning the arrangement of hyperplanes. For ease of exposition, con-  
 708 sider the nonnegative orthant  $O^+ = \mathbb{R}_{\geq 0}^{|A|}$ . Using the flow function  $q(\cdot)$  as defined in  
 709 subsection 4.1.2, fixing the flow direction to this orthant amounts to the constraint  
 710  $q(q_N) \in O$ , i.e.,  $q(q_N) \geq O$ . Each entry of  $q(\cdot)$  defines a hyperplane in  $\mathbb{R}^{|N|}$ . Consider  
 711 the regions that can arise by segmenting  $\mathbb{R}^{|N|}$  using the hyperplanes in  $q(\cdot)$ . For all  
 712  $a \in A$ , each region is a subset of either  $q_a(q_N) < 0$  or  $q_a(q_N) > 0$ . Therefore, the  
 713 flow direction on all arcs in the graph is constant on each region. The total num-  
 714 ber of regions that can be constructed in  $\mathbb{R}^{|N|}$  using  $|A|$  hyperplanes is bounded by  
 715  $\sum_{i=0}^{|N|} \binom{|A|}{i} \in \mathcal{O}(|A|^{|N|})$  ([30]). Furthermore, constructing all regions can be achieved  
 716 in run time  $\mathcal{O}(|A|^{|N|})$  using the algorithm of [6].  $\square$

717 However, there is an issue arising with this approach as the subproblems are of  
718 the type (see [Lemma 3.7](#))

$$719 \quad \text{Proj}_u(\mathcal{G}_U \cap O_i) \subseteq \text{Proj}_u(\mathcal{G}_U \cap \mathcal{H} \cap O_i).$$

720 The feasibility method can be employed as-is since optimizing over a projection set  
721 poses no restriction. On the other hand, the infeasibility method can not be applied  
722 as easily since it requires the moments over the uncertainty set. In case of the given  
723 subproblems, this is the set  $\text{Proj}_u(\mathcal{G}_U \cap O_i)$ . In general, it is unclear how the moments  
724 can be obtained without explicitly constructing the projection. Nevertheless, this  
725 is possible for networks with one cycle. The next section gives the description of  
726  $\text{Proj}_u(\mathcal{G}_U \cap O_i)$  for this case. In this setting, the infeasibility method can be applied  
727 since the projected set is polyhedral.

728 **4.3.3. Elimination by Case Distinction: a Shortcut for Networks with**  
729 **One Cycle.** On networks with only one cycle, a considerable simplification can be  
730 applied. The absolute values can be eliminated by restricting the problem to certain  
731 subsets of the uncertainty set. In contrast, the previous case distinction method relied  
732 on restricting the flow variables. The advantage of using subsets of the uncertainty  
733 set for this purpose is that the infeasibility method can be applied as well since it  
734 requires explicit knowledge of the uncertainty set.

735 For the purpose of this chapter, we assume a directed cyclic graph where each arc  
736 points to a different node:

737 **ASSUMPTION 4.8.** Let  $G = (V, A)$  be a directed cyclic graph with  $V = \{0, \dots, n\}$ ,  
738  $A = \{(0, 1), (1, 2), \dots, (n-1, n), (n, 0)\}$ , and nonzero demand  $q^{\text{nom}+} \in \mathbb{R}^{|V|}$ .

739 Due to the cyclic structure, the arcs can be uniquely identified by their first node.  
740 We assume the last edge to be part of the nonbasis, thus there is only one problem  
741 variable  $q_n \in \mathbb{R}$  with  $q_N \equiv q_n$ . Employing a very similar construction as [8, Chapter  
742 6.1], we obtain the set  $\mathcal{G}$  of feasible  $(\phi, q_n)$ -combinations and the associated cycle flow  
743 equation:

744 **PROPOSITION 4.9.** Let [Assumption 4.8](#) be satisfied.

745 Then  $\mathcal{G} = \left\{ \phi \in \mathbb{R}_{>0}^{|A|}, q_n \in \mathbb{R} \mid h(\phi, q_n) = 0 \right\}$  with

$$746 \quad h(\phi, q_n) := - \sum_{a \in A} f(q_a) = - \sum_{a \in A} f(q_n - \beta_a)$$

747 and  $\beta_a \in \mathbb{R}$  for  $a \in A$ . The constraint  $h(\phi, q_n) = 0$  is the so-called cycle flow equation.

748 Using  $h$ , a characterization of the set of all pressure loss coefficients  $\phi$  which lead to  
749 the flow  $q_n$  being bounded in some interval can be found:

750 **LEMMA 4.10.** Let [Assumption 4.8](#) be satisfied. Let  $\underline{q}_n, \bar{q}_n \in \mathbb{R}$ ,  $\phi \in \mathbb{R}_{>0}^{|A|}$  and let  $h$   
751 be as in [Proposition 4.9](#). Then

$$752 \quad \{ \phi \mid h(\phi, q_n) = 0 \text{ for some } q_n \in [\underline{q}_n, \bar{q}_n] \} = \{ \phi \mid h(\phi, \bar{q}_n) \leq 0, h(\phi, \underline{q}_n) \geq 0 \}.$$

753 *Proof.* For constant  $\phi \in \mathbb{R}_{>0}^{|A|}$ , the function  $h(\phi, q_n)$  is monotonically decreasing  
754 in  $q_n$  since

$$755 \quad \frac{d}{dq_n} h(\phi, q_n) = - \sum_{i=0}^n \phi_i \frac{d}{dq_n} f(q_n - \beta_i) = - \sum_{i=0}^n \phi_i 2 |q_n - \beta_i| \leq 0.$$

756 Furthermore,  $\lim_{q_n \rightarrow \pm\infty} h(\phi, q_n) = \mp\infty$ .

757 Let  $A := \{\phi \in \mathbb{R}_{>0}^{|A|} \mid h(\phi, q_n) = 0, \underline{q}_n \leq q_n\}$  and  $B := \{\phi \in \mathbb{R}_{>0}^{|A|} \mid h(\phi, \underline{q}_n) \geq 0\}$ .  
 758 We show  $A = B$  first:

759 “ $\Rightarrow$ ”: Pick  $\phi \in A$ . By definition of  $A$ , there is  $\underline{q}_n \leq q_n$  with  $h(\phi, q_n) = 0$ . Since  
 760  $h(\phi, \cdot)$  is monotonically decreasing,  $h(\phi, \underline{q}_n) \geq h(\phi, q_n) = 0$ . Therefore  $\phi \in B$ .

761 “ $\Leftarrow$ ”: Pick  $\phi \in B$ . Since  $h$  is continuous,  $h(\phi, \underline{q}_n) \geq 0$ , and  $\lim_{q_n \rightarrow \infty} h(\phi, q_n) =$   
 762  $-\infty$ , the intermediate value theorem implies a  $h(\phi, q_n) = 0$ . Therefore  $\phi \in A$ .

763 This shows  $A = B$ . There is a similar result where the inequalities in the defini-  
 764 tions of  $A, B$  are flipped. Together, both results prove that

$$765 \quad \left\{ \phi \in \mathbb{R}_{>0}^{|A|} \mid h(\phi, q_n) = 0, q_n \in [\underline{q}_n, \bar{q}_n] \right\} = \left\{ \phi \in \mathbb{R}_{>0}^{|A|} \mid h(\phi, \bar{q}_n) \leq 0, h(\phi, \underline{q}_n) \geq 0 \right\}. \quad \square$$

766 With this lemma, restricting  $q_n$  to a given interval can be expressed equivalently by  
 767 restricting the considered pressure loss coefficients  $\phi$ . Furthermore, the constraints  
 768 for  $\phi$  are hyperplanes in  $\mathbb{R}^{|A|}$  as  $h(\phi, q_n)$  is linear in  $\phi$ .

769 We adapt a procedure from [8, Proposition 5] to our setting in order to identify  
 770 intervals for the flow  $q_n$  that guarantee constant flow direction on all arcs of the  
 771 network. Once the possible subsets are identified, we apply Lemma 4.10 to relate the  
 772 obtained flow intervals to subsets in the space of the uncertainty.

773 The absolute value functions only occur in the form  $\phi|q_a|(q_a)$ . From Proposition 4.9,  
 774 the flow  $q_a$  along an arc  $a \in A$  is given by

$$775 \quad q_a(q_n) = q_n - \beta_a.$$

776 Therefore, the absolute value  $|q_a(q_n)|$  can be eliminated by restricting the flow  $q_n$   
 777 to either  $q_n \geq \beta_a$  or  $q_n \leq \beta_a$ . Next, reorder  $\beta_0, \beta_1, \dots, \beta_n$  such that  $\beta_{i_0} \leq \beta_{i_1} \leq$   
 778  $\dots \leq \beta_{i_n}$ . With this in mind, taking any consecutive pair  $\beta_{i_j}, \beta_{i_{j+1}}$  yields an interval  
 779 for  $q_n$  such that the flow over the whole network is constant. Due to [8] and the  
 780 nonzero demand from Assumption 4.8, the solutions of  $h(\phi, q_n) = 0$  can only be  
 781 within  $[\beta_{i_0}, \beta_{i_n}]$  for any fixed  $\phi$ . Therefore, the absolute values can be eliminated by  
 782 restricting  $q_n$  to the intervals

$$783 \quad [\beta_{i_0}, \beta_{i_1}], \quad [\beta_{i_1}, \beta_{i_2}], \quad \dots \quad [\beta_{i_{n-1}}, \beta_{i_n}].$$

785 Applying Lemma 4.10 to these intervals yields an equivalent condition for constant  
 786 flow directions in the space of the uncertainty.

787 PROPOSITION 4.11. *Let Assumption 4.8 be satisfied and let*

$$788 \quad \mathcal{U}_j := \mathcal{U} \cap \left\{ \phi \in \mathbb{R}_{>0}^{|A|} \mid h(\phi, \beta_{i_{j+1}}) \leq 0, h(\phi, \beta_{i_j}) \geq 0 \right\} \quad \text{for } j = 0, \dots, n-1.$$

789 *Then the set containment question  $\mathcal{U} \subseteq \text{Proj}_\phi(\mathcal{B}) = \text{Proj}_\phi(\mathcal{G}_\mathcal{U} \cap \mathcal{H})$  can be decided by*  
 790 *solving the subproblems*

$$791 \quad \mathcal{U}_j \subseteq \text{Proj}_\phi(\mathcal{G}_\mathcal{U}_j \cap \mathcal{H}) \quad \text{for } j = 0, \dots, n-1.$$

792 We remark that if  $\mathcal{U}$  is polyhedral then  $\mathcal{U}_j$  is polyhedral as well.

793 **5. Numerical Experiments.** In this section, some practical results of the feasi-  
 794 bility and infeasibility approaches on a set of small gas networks under uncertainty are  
 795 presented. Instead of considering arbitrary gas networks, we focus on highlighting our  
 796 methods’ performance on the core problem: deciding a single cycle under uncertainty.

797 Using [Lemma 4.6](#), the feasibility of any subtree in a given network can be reduced if  
 798 the pressure at the root node is contained in a pre-calculated interval. This allows  
 799 us to remove any subtree by updating the pressure bounds at the intersecting node  
 800 with the remaining network. Assuming there is only one remaining cycle, [Lemma 4.10](#)  
 801 is then used to split the problem into subproblems on subsets of the uncertainty set  
 802 while eliminating all absolute values. Since this just increases the number of problems  
 803 to consider but does not fundamentally change their nature, we start with a single  
 804 cycle and uncertainty sets that guarantee constant flow direction on all arcs.

805 The example networks are cyclic with nodes  $V = \{1, 2, \dots, n\}$  for  $n \in \{2, \dots, 7\}$   
 806 and arcs  $A = \{(1, 2), (2, 3), \dots, (n - 1, n), (n, 1)\}$ . A family of uncertainty sets is  
 807 considered:

$$808 \quad \mathcal{U}(c) = \times_{a \in A} [1, c], \quad c \in [2, 4].$$

809 Furthermore, define two special uncertainty sets,

$$810 \quad \mathcal{U}_{\text{feas}} := \mathcal{U}(2) \quad \text{and} \quad \mathcal{U}_{\text{infeas}} := \mathcal{U}(4),$$

811 which we want to investigate with respect to feasibility and infeasibility, respectively.

812 [Table 1](#) shows the parameters of the considered instances. The columns denote  
 813 the nodes within the network. Each row denotes the specific instance with  $n$  nodes.  
 814 Within each row, the demand and bounds of the squared pressure  $\pi$  at each node is  
 815 displayed in the first and second lines, respectively.

TABLE 1  
 Demand and squared pressure bounds  $\pi$  per node  $v$  for each test network.

		node $v \in V$						
		1	2	3	4	5	6	7
n=2	demand	-10	10					
	$\pi$ -bounds	[0, 200]	[140, 200]					
n=3	demand	-10	2	8				
	$\pi$ -bounds	[0, 200]	[0, 200]	[130, 200]				
n=4	demand	-10	2	6	2			
	$\pi$ -bounds	[0, 200]	[0, 200]	[115, 200]	[0, 200]			
n=5	demand	-10	1	1	6	2		
	$\pi$ -bounds	[0, 200]	[0, 200]	[0, 200]	[100, 200]	[0, 200]		
n=6	demand	-10	1	1	6	1	1	
	$\pi$ -bounds	[0, 200]	[0, 200]	[0, 200]	[70, 200]	[0, 200]	[0, 200]	
n=7	demand	-10	1	1	1	4	2	1
	$\pi$ -bounds	[0, 200]	[0, 200]	[0, 200]	[0, 200]	[50, 200]	[0, 200]	[0, 200]

816 Every network's  $\mathcal{H}$ -set (see Subsection [4.1.5](#)) is made up of  $n(n - 1)$  inequalities  
 817  $h_i$  ( $i \in I$ ). Each inequality is checked for *feasibility* using ([MinCons](#)); all inequalities  
 818 are checked at once for *infeasibility* using ([PolySepProj](#)). Both optimization tasks are  
 819 solved using SDP relaxations of the problems. We remark that ([PolySepProj](#)) could  
 820 be applied to all constraints individually. However, experiments show that solving  
 821 the problem for a single constraint individually is only marginally faster than solving  
 822 the problem for all constraints at once. Therefore, we solve the infeasibility problem  
 823 once with all constraints combined rather than up to  $|I|$  subproblems by considering  
 824 each constraint on its own.

TABLE 2

Objectives of the feasibility method solving (MinCons) and infeasibility method solving (PolySepProj) for the three node instance over  $\mathcal{U}_{\text{infeas}}$ . Each row in the feasibility group denotes the subproblem with objective function  $h_i$ .

i	feasibility		infeasibility	
	level 2	level 3	level 2	level 3
1	<b>216.89</b>	217.39		
2	<b>53.09</b>	-		
3	<b>228.63</b>	228.63		
4	-116.79	-	0.00	<b>unbnd</b>
5	<b>201.67</b>	-		
6	-35.99	<b>20.34</b>		

825 All experiments were carried out on a notebook with four Intel i7-4810MQ cores  
 826 running at 2.80GHz each and 16 GB of RAM. The methods were implemented using  
 827 MATLAB R2016b. GloptiPoly 3.8 [10] was used for the feasibility models since it  
 828 provides a straight forward interface for solving polynomial optimization problems.  
 829 Since the infeasibility method exceeds the capabilities of GloptiPoly, this approach  
 830 was implemented using the SOS-module of YALMIP R20160930 [16]. The resulting  
 831 SDP problems were solved with MOSEK 8 [18] using 4 threads.

832 Some problems were not solvable with the desired precision. This happened al-  
 833 though we evaluated the problems on a variety of solvers including SeDuMi [27] and  
 834 SDPT3 [28] as well as on a third modeling tool, SOSTOOLS [20]. The chosen com-  
 835 bination of MOSEK with GloptiPoly and YALMIP offered the most robust behavior  
 836 amongst all considered possibilities.

837 **5.1. Effectiveness of the Methods.** The effectiveness of both methods can be  
 838 measured in the typical running times of the semidefinite subproblems as well as in  
 839 hierarchy level at which set containment can be decided.

840 First, the results of both methods on a fixed network are presented. Table 2 shows  
 841 the outcome of both methods for the  $n = 3$  instance over  $\mathcal{U}_{\text{infeas}}$ . The columns are sep-  
 842 arated into groups concerning the feasibility method (MinCons) and the infeasibility  
 843 method (PolySepProj) with a further distinction into the employed hierarchy level.  
 844 The rows in the feasibility part denote the constraint  $h_i$  which is minimized. Since  
 845 the infeasibility method is applied to all constraints at once, there is only one row of  
 846 results in the infeasibility part of the table. Cells marked by “-” indicate numerical  
 847 difficulties, i.e., we were unable to solve the specific problem to the desired precision.  
 848 The feasibility approach has a positive objective for five out of six subproblems, thus  
 849 confirming set containment for those constraints. Out of these five problems, four were  
 850 decided on the second hierarchy level while one required a level 3 solution. When ap-  
 851 plying the infeasibility approach, the level 3 model is unbounded, thereby refuting set  
 852 containment. Over all, the instance therefore isn’t robust feasible.

853 Next, the required levels of the relaxation hierarchy are evaluated. For this pur-  
 854 pose, each constraint of each instance is considered for set containment while gradually  
 855 increasing the hierarchy level from two to four. Once a subproblem is solved success-  
 856 fully, the corresponding number of solved problems on this specific level is incremented  
 857 in the table.

858 Table 3 contains the feasibility methods’ results for all instances on the smaller  
 859 uncertainty set  $\mathcal{U}_{\text{feas}}$ . Each row denotes the considered instance with  $n$  nodes and a

TABLE 3

For a given instance with  $n$  nodes, count how many subproblems out of  $I$  were solved successfully using the feasibility method. Positive outcomes of each subproblem are counted only once on the smallest level. All instances were solved over the  $\mathcal{U}_{feas}$  uncertainty set.

n	$ I $	level 2	level 3	level 4
2	2	1	1	0
3	6	5	1	0
4	12	11	1	0
5	20	19	1	0
6	30	29	1	0
7	42	42	0	0

total of  $|I|$  subproblems. The columns indicate how many of the feasibility problems were solved successfully on the respective level. For any subproblem, only the first success is counted, thus the sum of each row can be at most  $|I|$ . If the row-wise sum is less than  $|I|$ , this implies that some problems were not solvable with the desired precision.

It can be observed that the feasibility approach almost exclusively confirms set containment at the second level. At most one subproblem per instance required solving of a level 3 problem. As suspected, all instances are robust feasible with this uncertainty region.

Using the larger uncertainty set  $\mathcal{U}_{infeas}$ , both the feasibility and the infeasibility method were applied to all instances. Table 4 summarizes all results. Each row denotes the considered instance with  $n$  nodes. The columns are separated into groups according to the employed method with further distinction for the used hierarchy level. Each column in the feasibility group indicates how many of the feasibility problems were solved successfully. For any subproblem, only the first success is counted, therefore the sum of each row in the feasibility group can be at most  $|I|$ . The columns in the infeasibility group denote the status of the corresponding problem. Cells marked with “zero obj.” indicate global optimality of the considered problem but an objective value of zero, which is insufficient to show certify infeasibility. Cells marked with a checkmark (✓) represent an unbounded objective and thus a negative answer to the set containment question. As usual, “-” marks numerical difficulties.

Many feasibility problems were solved successfully at the second hierarchy level. Set containment of some constraints could not be confirmed with the feasibility method using the given levels. This is either due to numerical problems or negative objective values. However, for almost all instances, the infeasibility method was able to provide a certificate against set containment using the third hierarchy level relaxation. This shows that  $\mathcal{U}_{infeas}$  is robust infeasible for the  $n = 2, \dots, 6$  instances.

To conclude this set of test runs, Tables 5 and 6 show the characteristic run times where each row denotes the  $n$ -node instance. For the feasibility approach, the columns show mean run time and standard deviation using the specific relaxation hierarchy level. All values are aggregated over all subproblems of the given instance and hierarchy level. Since the infeasibility approach is a single problem when instance and hierarchy level are fixed, no aggregation is possible and we show the run time as-is. It can be observed that the run times are quite small for the level 2 problems but increase quickly for higher levels and larger instances.

TABLE 4

For a given instance with  $n$  nodes, count how many subproblems of  $I$  were solved successfully using the feasibility method. For each subproblem, a positive outcome is counted only once on the smallest level. The results of the infeasibility method are displayed in the right column group. All instances were solved over the  $\mathcal{U}_{\text{infeas}}$  uncertainty set.

n	I	feasibility			infeasibility		
		level 2	level 3	level 4	level 2	level 3	level 4
2	2	1	0	0	zero obj.	✓	✓
3	6	4	1	0	zero obj.	✓	✓
4	12	9	1	0	zero obj.	✓	✓
5	20	16	1	0	zero obj.	✓	✓
6	30	25	1	0	zero obj.	✓	✓
7	42	36	2	0	zero obj.	-	-

TABLE 5

Mean and standard deviation of the feasibility method's run time on  $\mathcal{U}_{\text{feas}}$ . Each row shows the aggregated values for all subproblems of the  $n$ -node instance per hierarchy level.

n	level 2		level 3		level 4	
	mean	std	mean	std	mean	std
2	0.032 s	0.019 s	0.042 s	0.014 s	0.111 s	0.021 s
3	0.040 s	0.010 s	0.111 s	0.070 s	0.605 s	0.083 s
4	0.048 s	0.015 s	0.324 s	0.030 s	3.899 s	0.187 s
5	0.083 s	0.024 s	1.229 s	0.185 s	26.679 s	3.040 s
6	0.147 s	0.047 s	4.533 s	0.894 s	148.397 s	9.500 s
7	0.241 s	0.061 s	15.721 s	2.328 s	809.944 s	71.564 s

895 **5.2. Evaluation of the Gap Between Methods.** The proposed methods are  
 896 based on semidefinite relaxations of polynomial problems (see [subsection 2.2](#)). Since  
 897 the objective values of relaxed problems are smaller or equal than the non-relaxed  
 898 optimal values (for minimization problems), it is expected that the feasibility and  
 899 infeasibility approach can decide a smaller number of problems than their non-relaxed  
 900 counterparts. The aim of this section is to investigate how large the “gap” between  
 901 feasibility and infeasibility approach is. After fixing a hierarchy level, all problems  
 902 which cannot be decided by either feasibility or infeasibility approach are said to fall  
 903 into this relaxation gap. In order to compare both methods, we need to apply the  
 904 infeasibility approach to the same constraint as the feasibility method. This is different  
 905 to all previous tests where the infeasibility method was solved for all constraints at  
 906 once.

907 Consider the parameterized uncertainty set  $\mathcal{U}(c)$  for increasing  $c \in [2, 4]$ . From  
 908 [Table 3](#), it can be derived that all subproblems are feasible for  $\mathcal{U}_{\text{feas}} = \mathcal{U}(2)$ . On the  
 909 other hand, as [Table 4](#) shows, all instances are infeasible for the larger  $\mathcal{U}_{\text{infeas}} = \mathcal{U}(4)$ .  
 910 This implies that there is always at least one violated constraint  $h_i$  when using  $\mathcal{U}(4)$ .

911 For this test set, we select one subproblem per instance that is infeasible for the  
 912 larger uncertainty set. Then, the feasibility and infeasibility approaches are solved  
 913 for the selected subproblems over all twenty uncertainty sets  $\mathcal{U}(c)$  for  $c = 2 + i\frac{1}{10}$ ,  
 914  $i = 0, \dots, 20$ . [Figure 1](#) shows the results in more detail for the four node instance.  
 915 We consider the subproblem that is marked as infeasible in [Table 4](#). The objective




TABLE 6

Runtime of the infeasibility method on  $\mathcal{U}_{infeas}$  where each row denotes the  $n$ -node instance and each column the respective level.

n	level 2	level 3	level 4
2	0.415 s	0.564 s	0.504 s
3	0.435 s	0.501 s	0.849 s
4	0.433 s	0.771 s	3.909 s
5	0.390 s	1.854 s	20.203 s
6	0.432 s	4.915 s	134.531 s
7	0.643 s	10.281 s	975.161 s

FIG. 1. Objective values of the two methods for varied  $c \in \{2.0, 2.1, \dots, 4\}$  on the four node instance.



916 values of the feasibility problem (**MinCons**) are marked with blue (level 2) and orange  
 917 (level 3) triangles in the figure. Additionally, the values of solving (**PolySepProj**) are  
 918 marked using red (level 3) and purple (level 4) circles. We remark that the outcome  
 919 of the infeasibility method for level 2 is omitted since as all subproblems were feasible  
 920 but had objective value of zero. Unbounded subproblems of the infeasibility method  
 921 are marked with an objective value of fifteen times their level. Missing data points  
 922 can be attributed to numerical difficulties of the SDP solver.

923 As can be observed, no instance can be decided on the second hierarchy level  
 924 since all solutions of the feasibility method have negative objective values and all  
 925 solutions of the infeasibility method have objective value zero (not shown in the  
 926 figure). On the third hierarchy level, the feasibility approach confirms set containment  
 927 for  $c \in \{2.0, 2.1, \dots, 2.5\}$  as these problems have positive objective value. With the  
 928 same level, the infeasibility approach finds certificates against set containment for  
 929  $c \in \{3.4, \dots, 4.0\}$ . For the problems with  $c \in \{2.6, \dots, 3.3\}$ , neither of the methods

TABLE 7

Extreme values for  $c$  where the feasibility ( $c_{\text{feas}}$ ) and infeasibility ( $c_{\text{infeas}}$ ) methods can solve the problem.

n	level 3			level 4		
	$c_{\text{feas}}$	$c_{\text{infeas}}$	gap	$c_{\text{feas}}$	$c_{\text{infeas}}$	gap
2	2.4	3.3	0.9	2.4	2.9	0.5
3	2.4	3.2	0.8	2.4	3.1	0.7
4	2.5	3.4	0.9	2.5	3.2	0.7
5	2.4	3.4	1.0	2.4	3.3	0.9
6	2.6	3.7	1.1	3.1	3.6	0.5
7	3.0			3.3		

930 was able to decide set containment successfully (disregarding numerical difficulties).  
 931 In this range, the feasibility method only returns negative objective values and all  
 932 objective values of the infeasibility method were zero.

933 Increasing the hierarchy level to four leads to numerical problems for all feasibility  
 934 models, but also increases the number of successfully solved infeasibility models by  
 935 two ( $c = 3.2$  and  $c = 3.3$ ). This confirms the expectation that increasing the hierarchy  
 936 level can lead to more certificates for non-set containment.

937 The results over all instances is summarized in Table 7. For each hierarchy level, it  
 938 shows both the largest value for  $c$  (indicated by  $c_{\text{feas}}$ ) such that the feasibility approach  
 939 confirms set containment and the smallest value for  $c$  (indicated by  $c_{\text{infeas}}$ ) where  
 940 a certificate for infeasibility could be obtained. Note that these bounds on  $c$  take  
 941 all smaller hierarchy levels into account as well. The gap column is the difference  
 942  $c_{\text{infeas}} - c_{\text{feas}}$  and indicates the range of problems which could not be solved successfully  
 943 with either feasibility and infeasibility approach. Again it can be observed that the  
 944 gap is reduced after increasing the hierarchy level as this leads to a tighter relaxation  
 945 for the feasibility approach and admits a richer set of polynomials for the infeasibility  
 946 certificate.

947 **6. Concluding Remarks.** In this paper, we study feasibility and infeasibility  
 948 of nonlinear two-stage fully adjustable robust feasibility problems with an empty first  
 949 stage. We propose to solve this problem by deciding whether the given uncertainty set  
 950 is a subset of the projection of all feasible (uncertainty, solution)-pairs. A particular  
 951 challenge with this approach is given by the projected set whose defining constraints  
 952 are typically not available. Compared to typical methods from robust optimization,  
 953 our approach requires no additional restrictions such as like convexity of the prob-  
 954 lem or the uncertainty set. Furthermore, it can decide the fully adjustable problem  
 955 without using (possible approximative) decision rules for the second stage variables.  
 956 We develop two approaches towards solving this problem, one for deciding feasibility  
 957 and one for deciding infeasibility. As we solve relaxations of the proposed methods  
 958 in practice, two distinct methods are necessary since a single method cannot be ex-  
 959 pected to solve both sides of the question. The first approach for deciding infeasibility  
 960 uses a separation argument to find polynomial that certifies violation of the set con-  
 961 tainment question. The second approach is based the assumption that part of the  
 962 problem constraints define a unique solution for a fixed element of the uncertainty  
 963 set. Exploiting this fact allows a reformulation as a set containment question over two  
 964 regular (non-projected) sets. Set containment can then be confirmed by minimizing

965 the constraint functions of the superset over the subset. In our setting, both methods  
 966 lead to polynomial optimization problems. For solving the polynomial problems in  
 967 practice, we fall back onto the Lasserre SDP relaxation hierarchy.

968 The proposed models are then applied to an uncertain gas transport problem.  
 969 This is a non-convex quadratic problem with absolute value functions. First, we show  
 970 how this problem can be decided exactly on tree structured using LP duality to decide  
 971 set containment of polyhedra. Next, this result is used to preprocess larger problems  
 972 so that only cycles remain. Lastly, we present different ideas how to remove the  
 973 absolute values functions from the problem formulation. By removing the absolute  
 974 values, the problem is transformed to a purely polynomial description to which the  
 975 proposed methods can be applied.

976 Both approaches are then solved on a set of cyclic test networks. For problems  
 977 where deciding robustness was possible, we observe that typically level 2 or level 3  
 978 of the Lasserre hierarchy were sufficient. We further investigate the strength of the  
 979 relaxation by searching for uncertainty sets where neither feasibility nor infeasibility  
 980 can be decided for a given instance and hierarchy level. As can be expected, increasing  
 981 the level yields tighter relaxations which translates into a more effective method.

982 As an outlook, the developed ideas could be applied to similar potential driven  
 983 network flow problems such as e.g., the DC optimal power problem flow or water  
 984 network problems. Concerning the application to gas networks, extending the relation  
 985 between subsets of the uncertainty set and flow directions to networks with multiple  
 986 intermeshed cycles is another relevant question. Lastly, using the feasibility methods  
 987 as part of a larger two-stage robust optimization task with non empty first stage  
 988 provides another possible extension of the studied problem. In case of gas, first stage  
 989 variables model decisions of the network operator e.g., the compressor machines' power  
 990 level.

991 **Acknowledgments.** The authors thank Prof. Dick den Hertog for fruitful dis-  
 992 cussions on the topic.

993

## REFERENCES

- 994 [1] *Evaluating gas network capacities*, 2015, <https://doi.org/10.1137/1.9781611973693>.  
 995 [2] A. BEN-TAL, D. DEN HERTOOG, AND J. P. VIAL, *Deriving robust counterparts of nonlinear un-*  
 996 *certain inequalities*, 149 (2015), pp. 265–299, <https://doi.org/10.1007/s10107-014-0750-8>.  
 997 [3] A. BEN-TAL, A. GORYASHKO, E. GUSLITZER, AND A. NEMIROVSKI, *Adjustable robust so-*  
 998 *lutions of uncertain linear programs*, 99 (2004), pp. 351–376, <https://doi.org/10.1007/s10107-003-0454-y>.  
 1000 [4] G. E. COLLINS, *Quantifier elimination for real closed fields by cylindrical algebraic decompos-*  
 1001 *tion*, Springer, 1975, pp. 134–183, [https://doi.org/10.1007/3-540-07407-4\\_17](https://doi.org/10.1007/3-540-07407-4_17).  
 1002 [5] M. COLLINS, L. COOPER, R. HELGASON, J. KENNINGTON, AND L. LEBLANC, *Solving the pipe*  
 1003 *network analysis problem using optimization techniques*, 24 (1978), pp. 747–760, <https://doi.org/10.1287/mnsc.24.7.747>.  
 1004 [6] H. EDELSBRUNNER, J. O'ROURKE, AND R. SEIDEL, *Constructing arrangements of lines and*  
 1005 *hyperplanes with applications*, 15 (1986), pp. 341–363, <https://doi.org/10.1137/0215024>.  
 1006 [7] B. GEISSLER, *Towards globally optimal solutions for MINLPs by discretization techniques with*  
 1007 *applications in gas network optimization*, PhD thesis.  
 1008 [8] C. GOTZES, H. HEITSCH, R. HENRION, AND R. SCHULTZ, *On the quantification of nomination*  
 1009 *feasibility in stationary gas networks with random load*, 84 (2016), pp. 427–457, <https://doi.org/10.1007/s00186-016-0564-y>.  
 1010 [9] P. GRITZMANN AND V. KLEE, *On the complexity of some basic problems in computational*  
 1011 *convexity: I. containment problems*, 136 (1994), pp. 129–174, [https://doi.org/10.1016/0012-365X\(94\)00111-U](https://doi.org/10.1016/0012-365X(94)00111-U).  
 1012 [10] D. HENRION, J. B. LASSERRE, AND J. LÖFBERG, *GloptiPoly 3: moments, optimiza-*  
 1013 *tion and semidefinite programming*, 24 (2009), pp. 761–779, <https://doi.org/10.1080/>

- 1017 [10556780802699201](https://doi.org/10.556780802699201).
- 1018 [11] Z. JARVIS-WLOSZEK, R. FEELEY, W. T., K. SUN, AND A. PACKARD, *Some controls applications*
- 1019 *of sum of squares programming*, in 42<sup>nd</sup> IEEE International Conference on Decision and
- 1020 Control, vol. 5, IEEE, 2003, pp. 4676–4681, <https://doi.org/10.1109/CDC.2003.1272309>.
- 1021 [12] K. KELLNER, *Positivstellensatz certificates for containment of polyhedra and spectrahedra*, PhD
- 1022 thesis.
- 1023 [13] K. KELLNER, T. THEOBALD, AND C. TRABANDT, *Containment problems for polytopes and*
- 1024 *spectrahedra*, 23 (2013), pp. 1000–1020, <https://doi.org/10.1137/120874898>.
- 1025 [14] J. B. LASSERRE, *Global optimization with polynomials and the problem of moments*, 11 (2001),
- 1026 pp. 796–817, <https://doi.org/10.1137/S1052623400366802>.
- 1027 [15] J. B. LASSERRE AND T. NETZER, *SOS approximations of nonnegative polynomials via*
- 1028 *simple high degree perturbations*, 256 (2007), pp. 99–112, [https://doi.org/10.1007/](https://doi.org/10.1007/s00209-006-0061-8)
- 1029 [s00209-006-0061-8](https://doi.org/10.1007/s00209-006-0061-8).
- 1030 [16] J. LÖFBERG, *Pre- and post-processing sum-of-squares programs in practice*, 54 (2009), pp. 1007–
- 1031 1011, <https://doi.org/10.1109/TAC.2009.2017144>.
- 1032 [17] O. L. MANGASARIAN, *Set containment characterization*, 24 (2002), pp. 473–480, [https://doi.](https://doi.org/10.1023/A:1021207718605)
- 1033 [org/10.1023/A:1021207718605](https://doi.org/10.1023/A:1021207718605).
- 1034 [18] MOSEK, *The MOSEK optimization toolbox for MATLAB manual*, 2011.
- 1035 [19] Y. NESTEROV, *Squared functional systems and optimization problems*, Springer US, 2000,
- 1036 pp. 405–440, [https://doi.org/10.1007/978-1-4757-3216-0\\_17](https://doi.org/10.1007/978-1-4757-3216-0_17).
- 1037 [20] A. PAPACHRISTODOULOU, J. ANDERSON, G. VALMORBIDA, S. PRAJNA, P. SEILER, AND P. A.
- 1038 PARRILO, *Sostools: sum of squares optimization toolbox for matlab*, 2013. Available from
- 1039 [eng.ox.ac.uk/control/sostools](http://eng.ox.ac.uk/control/sostools).
- 1040 [21] P. A. PARRILO, *Semidefinite programming relaxations for semialgebraic problems*, 96 (2003),
- 1041 pp. 293–320, <https://doi.org/10.1007/s10107-003-0387-5>.
- 1042 [22] M. E. PFETSCH, A. FÜGENSCHUH, B. GEISSLER, N. GEISSLER, R. GOLLMER, B. HILLER,
- 1043 J. HUMPOLA, T. KOCH, T. LEHMANN, A. MARTIN, A. MORSI, J. RÖVEKAMP, L. SCHEWE,
- 1044 M. SCHMIDT, R. SCHULTZ, R. SCHWARZ, J. SCHWEIGER, C. STANGL, M. C. STEINBACH,
- 1045 S. VIGERSKE, AND B. M. WILLERT, *Validation of nominations in gas network optimization:*
- 1046 *models, methods, and solutions*, 30 (2015), pp. 15–53, [https://doi.org/10.1080/10556788.](https://doi.org/10.1080/10556788.2014.888426)
- 1047 [2014.888426](https://doi.org/10.1080/10556788.2014.888426).
- 1048 [23] M. PUTINAR, *Positive polynomials on compact semi-algebraic sets*, Indiana University Mathe-
- 1049 matics Journal, 42 (1993), pp. 969–984.
- 1050 [24] R. Z. RÍOS-MERCADO AND C. BORRAZ-SÁNCHEZ, *Optimization problems in natural gas trans-*
- 1051 *portation systems: A state-of-the-art review*, 147 (2015), pp. 536–555.
- 1052 [25] R. Z. RÍOS-MERCADO, S. WU, L. R. SCOTT, AND E. A. BOYD, *A reduction technique for*
- 1053 *natural gas transmission network optimization problems*, 117 (2002), pp. 217–234, [https:](https://doi.org/10.1023/A:1021529709006)
- 1054 [//doi.org/10.1023/A:1021529709006](https://doi.org/10.1023/A:1021529709006).
- 1055 [26] N. Z. SHOR, *Class of global minimum bounds of polynomial functions*, 23 (1987), pp. 731–734.
- 1056 [27] J. F. STURM, *Using SeDuMi 1.02, a MATLAB toolbox for optimization over symmetric cones*,
- 1057 11 (1999), pp. 625–653, <https://doi.org/10.1080/10556789908805766>.
- 1058 [28] K. C. TOH, M. J. TODD, AND R. H. TÜTÜNCÜ, *SDPT3 — a matlab software package for*
- 1059 *semidefinite programming, version 1.3*, 11 (1999), pp. 545–581, [https://doi.org/10.1080/](https://doi.org/10.1080/10556789908805762)
- 1060 [10556789908805762](https://doi.org/10.1080/10556789908805762).
- 1061 [29] T. R. WEYMOUTH, *Problems in natural gas engineering*, 34 (1912), pp. 185–231.
- 1062 [30] T. ZASLAVSKY, *Facing up to arrangements: Face-count formulas for partitions of space by*
- 1063 *hyperplanes*, 1 (1975), <https://doi.org/10.1090/memo/0154>.